

# FRP Composite Bridges 2m to 30m Clear Span



# Contents

---

Sustainable Infrastructure Systems.....	7
High Tech Manufacturing & Quality Materials.....	8
Our Mission.....	10
About FiberCore Europe.....	11
Quality Systems Certification.....	13
What is Sustainable Infrastructure.....	14
InfraCore® Technology.....	15
Delamination & Cracking.....	16
Modular Construction.....	17
Maintenance Free.....	18
FRP Material.....	20
InfraCore® Technology.....	21
Typical Values.....	23
Codes & Standards.....	24
Fabrication.....	25
Resistance to Fatigue.....	26
Resistance to Impact.....	27
Built in Safety.....	28
Thermal Behaviour.....	29
Fire.....	30
Climate.....	31
Sustainability.....	32
Weights.....	33
Transport, Shipping & Lifting.....	34
Case Studies	
Staines Moore Bridge.....	44
Ordnance Bridge.....	62
Project Gallery.....	80
Cycleway Bridges.....	81
Golf Bridges.....	107
Port Bridges.....	111
Road Bridges.....	114



When you are ready to talk,  
contact our structures team  
to set a meeting, for samples  
or to discuss your project.



1300 26 10 74  
[service@sisau.com.au](mailto:service@sisau.com.au)  
[sisau.com.au](http://sisau.com.au)

Australian Head Office  
26 The Parade West  
Kent Town SA 5067



ADELAIDE | MELBOURNE | BRISBANE | SYDNEY | HONG KONG | SHANGHAI | SHENZHEN | LOS ANGELES



**Over 800 Structures  
Delivered  
Worldwide**

**Netherlands  
Belgium  
Norway  
Sweden  
Poland  
Australia  
UK, USA  
China**

**Available in Australia & New Zealand  
From Sustainable Infrastructure Systems (Aust.) Pty Ltd**



Welcome to the future  
of bridge building.



Until now, lightweight large single span composite bridges have not been available to designers, architects, engineers and stakeholders in Australia & New Zealand.

Sustainable Infrastructure Systems (SIS)  
is proud to introduce FiberCore Europe's  
InfraCore® Inside technology



# About Sustainable Infrastructure Systems (Aust.) Pty Ltd



SIS is a unique organisation focused on manufacturing and distributing sustainable and recycled products and projects for diversified clients around the world.

From recycled plastic, recycled wood plastic composites (WPC), fiberglass reinforced polymers (FRP) and recycled rubber through to our CoreSpan® co-extruded multi-composites and aluminum WPC hybrid composite and OEM manufacturing, SIS are market leaders in delivering sustainable products to customers in many markets.

SIS specialise in delivering our product range to markets including Civil Infrastructure, Building & Construction, Oil & Gas, Mining, Aviation, Aquaculture, Marine & Ports, Transport & Logistics and Agriculture.

# High Tech Manufacturing & Quality Materials



Products designed, manufactured and supplied by SIS embody state of the art technology and are engineered by our teams to deliver enhanced performance and sustainability effective operation for customers worldwide.

All our products are manufactured to the highest industry standards, following strict quality assurance guidelines. With many employees dedicated to production, quality product and technical expertise is ensured at all times.

Excellent long term relationships with our key suppliers of raw materials and components provide confidence in material quality as well as sustainable and efficient manufacturing and supply chain processes. The close relationship with our research and development division ensures that SIS manufacturing teams can react quickly and professionally to customer needs.

SIS has built a reputation based on excellent customer service, high quality manufacturing and on providing the right solution in sustainable product design and manufacturing.



Continuous improvement of equipment design, materials and manufacturing technology ensures SIS maintains its capability of offering clients the latest and most commercially viable sustainable products and projects available. SIS also works with clients to develop specific solutions to meet their unique needs through the application of research and development efforts in a partnering relationship.

We manufacture and supply products from materials that include:

- Recycled Plastic
- Fiberglass Reinforced Polymers
- Recycled Wood Plastic Composite
- Recycled Rubber
- Co-Extruded Aluminium / Wood Plastic Composite

With a global network of manufacturing facilities, along with projects delivered in Africa, the Middle East, Asia, Australia and the Pacific Rim, combined with over 20 years of composite experience, SIS can be trusted to provide easy, efficient and seamless supply to almost any place on earth.



# Our Mission

---

SIS aims to set a responsible standard of sustainable product design and manufacture and project delivery for our diverse client base in both the short and the long term.

We all have a significant impact on the world around us and each of us should play a part in protecting future generations. Designers, engineers and stake holders have a big responsibility to set standards of product and project design that benefits the environment and the people who live in it.

SIS' aspiration is that ultimately, talking about sustainability will become superfluous, because it will be the expected.





# About FiberCore Europe



In 1995, Jan Peeters developed Europe's first publicly accessible composite bridge in Harlingen. His engineering firm Composieten Team worked together on the project with the Dutch Department of Waterways.

Although composite is in many respects superior to concrete, wood and steel, the application of this great material in heavily loaded constructions requires extra attention.

Jan Peeters resigned from the Plastic and Rubber Institute at TNO and focused all his attention on developing a revolutionary construction technology with composite.

Despite the long history of composites, these high-tech materials had not been paid much attention. It took almost 10 years before the inventions of Jan Peeters could be applied in infrastructure.

Together with Simon de Jong, Jan Peeters founded FiberCore Europe in 2008.





With their patented technology InfraCore® Inside, FiberCore Europe is now a worldwide success.

More than 700 InfraCore® bridges, bridge decks and lock gates have been delivered in the Netherlands, Belgium, England, France, Italy, Sweden, Norway, China and the USA.

An important moment in the development of the company was the real scale research, which proved that the InfraCore® technology does not show any fatigue or any other structural failure for 100 years.

FiberCore Europe has grown steadily in recent years. Over the years, numerous patent positions were developed worldwide on the technology and the production method. 2015 showed company growth of over 140% and proved to be the real breakthrough, with the realisation of five moving road bridges and eight lock gates for the Wilhelmina Canal in Tilburg. After years of investment, the acceptance of the InfraCore® technology in civil infrastructure has become a reality.

Today, Jan Kroon is general manager of FiberCore Europe. Focus will be on further professionalisation and the ambitious (international) growth of the infrastructure company.



# Quality System Certification



The InfraCore® Inside technology was invented, developed and promoted by FiberCore Europe. It took a significant amount of time to come up with a structure that is cost effective to build, efficient in use, and best in bringing the potential of FRP to clients in the world of infrastructure.

FiberCore Europe operates an ISO9001 certified quality control system. The system ensures that products are built as specified and meet high quality standards. It includes everything from the supply of raw materials to verification of individual stages in the fabrication process.



# What is Sustainable Infrastructure

---

Sustainable infrastructure is not just about new infrastructure, it is about rehabilitation, reuse or the optimisation of existing infrastructure, which is consistent with the principles of sustainability and sustainable product development, whether it be from civil infrastructure to mining sectors.

This encompasses infrastructure renewal, long-term economic analysis of infrastructure, energy use and reduced infrastructure costs, the protection of existing infrastructure from environmental degradation, material selection for sustainability, quality, durability and energy conservation, minimising waste and materials, the redesign of infrastructure in light of climate change and the remediation of environmentally damaged areas of our world. Clearly, sustainable infrastructure will lead to improvements to society through better socio-economics. Responsible design needs to balance social, economic and environmental issues.





# InfraCore Technology



FiberCore Europe structures are made with our patented technology, InfraCore® Inside.

InfraCore® technology was specially developed for the construction of extremely strong panels made of fiber-reinforced polymer composite.

In order to guarantee this safety, all InfraCore® structures are provided with the InfraCore® Inside quality mark.

A close-up photograph of a dark, textured surface, likely a fiber-reinforced polymer composite panel. A large, embossed "InfraCore inside" logo is visible, with the words "InfraCore" in a larger font and "inside" in a smaller font. The logo is set within a rounded rectangular border.

# No Delamination or Cracking

In the past the weakness of regular composite constructions (sandwiches) was their delamination, a problem caused by the skin coming loose from the core.

Delamination mainly occurs after impact load, followed by fatigue load. In bridges this could be the case after cracking damage followed by passages with a wheel print.

InfraCore® technology is still the only technology that offers a solution for delamination. This solution cleared the way for the use of fiber reinforced polymers in Infrastructure.



# Modular Construction

The ability to construct elements off-site can dramatically improve how projects are delivered. Ultimately, this method of construction provides significant benefits when it comes to maximising speed and safety and minimising disruption. The low weight of InfraCore® elements and manufacturing off-site has some significant advantages;

- The disruption to surrounding road or rail infrastructure can be heavily reduced
- Safety risks for the construction of bridge elements are redirected towards the manufacturing plants - being controlled environments there is much less that can go wrong, when it comes to safety.
- Elements also benefit from being manufactured in a factory environment, avoiding the complications that can arise on a construction worksite.
- Production of bridge elements off-site means projects are more predictable when it comes to costs.
- Fewer labour elements necessary for constructing projects on site. This is a significant benefit when it comes to projects in congested or remote areas.
- Foundations required are approximately only one third of that required for concrete and steel constructions.
- The construction speed will minimise building time and road closures. For construction work that is well prepared, a bridge with InfraCore® Inside can be installed within one hour.
- As demand on scarce raw materials is reduced and emissions are very low, the technology is sustainable with regard to the environment.



# Maintenance Free & Guaranteed for 50 years

Structures with InfraCore® Inside require no maintenance after installation.

The materials used are not affected by moisture, rot, fungi, temperature, etc.

For this reason, InfraCore® elements are covered by a 50-year guarantee.

The outer surface of the bridges are finished in a high-quality gel coat or topcoat. As this finish is based on the same polymer as the bridge, they form one consistent unit.

InfraCore® is resistant to almost all forms of vandalism, such as graffiti and fire. Maintenance is limited to the cleaning and repair of the wearing surface. Repair will be required after the normal decrease of the roughness of the sacrificial layer.








# FRP Material

Fiber reinforced polymers are a composite material of structural fibers in a matrix of thermoset resin. The resin restrains the fibers against buckling and enables transfer of shear stress between the fibers. Thermoset resin does not get soft at elevated temperatures, unlike thermoplastic material in coffee cups and many household plastics.

The fibers in FRP are typically glass fibers, although also superior, generally more costly, carbon or aramid fibers can be used. Glass fibers have a strength of  $2800\text{N/mm}^2$  (or MPa) thus are stronger than steel ( $\sim 355\text{N/mm}^2$ ). Glass fibers are available as roving or as mat, either with fibers in one direction or combining a number of different directions. The fibers are like the reinforcement in reinforced concrete structures, yet at a much more refined level and entirely dispersed over the structure.




Overview of the Properties of InfraCore® Inside, with those applicable to civil engineering structures highlighted.

# InfraCore® - Technology

InfraCore® Inside is FiberCore Europe's proprietary technology to construct strong, lightweight and durable structures in FRP. The technology comprises of the design, the way the fibers are laid out and the method of fabrication.

While some freedom exists to tune the technology for each specific application, the fabrication follows a modular construction. The dimensional constraints are due to handling and transportation, but not the technology itself.

Structures manufactured using InfraCore® Inside technology are fully prefabricated and integral, with no internal bonding or bolting. The strength therefore relies on the fibers, which themselves are stronger than steel.




Rolls of glass fibers and an example of a glass fiber fabric comprising multiple fiber directions.






# InfraCore® Inside




The Principle of InfraCore® Inside :  
no skin-core debonding

The importance of strength being dominated by fibers means that a resin-dominated fracture path should be avoided, and it is demonstrated below:



In structures with fibers predominately in one direction, cracks eliminate the load distribution, and then propagate until failure. Fibers in cross-direction are essential to avoid this



In conventional sandwich structures, initial damage is propagated by rolling wheels, leading to skin-core debonding and total failure.



In InfraCore® Inside, local damage can not lead to catastrophic failure modes. Moreover, the core-material (foam) is not part of the load-bearing structure, but only acts as a placeholder during construction.

Mechanically behaves like a highly efficient sandwich structure.

In such structures, two skins are spaced in order to create a layer arm.

The space in between is filled with lightweight material that only transfers shear stresses.

The significance of InfraCore® Inside is that it incorporates a continuous structural connection between the two skins.

This eliminates the brittle failure as a result of debonding between skin and core.

# Typical Values

The properties of composite materials depend on the type, orientation and amount of fibers.

Typical values are as follows:

- Strength, span direction: 55N/mm<sup>2</sup> (or MPa)
- Strength, transverse: 150N/mm<sup>2</sup> (or MPa)
- Stiffness, span direction: 3900N/mm<sup>2</sup> (or 39GPa)
- Stiffness, transverse: 1100N/mm<sup>2</sup> (or 11GPa)

InfraCore® Inside technology is a modified and improved sandwich, significantly improved to eliminate the debonding between the core and the skins that is normally critical and fatal in sandwich construction. For preliminary design purposes it is usually sufficient to consider InfraCore® Inside as a sandwich typology, and ignore the contribution of the interior foam and webs.

InfraCore® Inside has so far been used to support vehicles of up to 60 tonnes.

The density of infused rigid solid FRP varies with the proportion of resin and fibers, but is normally between 1600 and 1800kg/m<sup>3</sup>. The bare core material, which has no structural role and only serves as a lost mould during construction, weighs 35kg/m<sup>3</sup>.



# Codes & Standards

While the design of FRP structures is not covered by the Eurocodes, the material independent parts of these codes can be used. The use of FRP is well established in naval and aerospace construction and abundant design experience is available. Design guidance that considers the specifics of FRP in civil engineering applications is available, the most advanced being the Dutch design guideline CUR 96-2017

Following the limit state design methodology of Eurocodes, it proposes reduction factors on theoretical material properties, depending on the application, the method of construction and the environment where it is applied. For the design of its InfraCore® Inside structure, FiberCore Europe follows the loadings set out in Eurocodes, and the checking as per the CUR 96-2017 guideline.


SIS engaged FMG Engineering to conduct a full review of the codes and compliance to Australian Standards and Codes.



# Fabrication

InfraCore® Inside is constructed with the vacuum infusion technique. This method allows fabricating integral structures in a structurally efficient way, in bespoke geometries.

The process involves transporting resin through a stack of glass fibers and foam blocks. The process takes place inside an airtight bag, with no emissions.



Schematic view of the vacuum infusion technique

Since InfraCore® Inside is a technology with the same principles at its core, it combines the fabrication efficiency of a system-based approach, with the flexibility of a customised fabrication method. The dimensions of the biggest element that can be produced are dictated by logistics, not by the technology itself.

Currently the maximum element length that can be manufactured is 56m and the maximum width 8m




# Resistance to Fatigue

When FRP is used in bridge construction, the design is most often governed by stiffness requirements.

In such stiff structures, the levels of strain are so low that the material is well outside the domain where it would be sensitive to fatigue.

FRP is also used in windmill blades. These endure much higher levels of stress and strain. From this application, a vast amount of information is available on fatigue behavior.

The resistance of InfraCore® Inside against fatigue has been comprehensively tested at Delft University of Technology. In the tests, a sample was subjected to a loading equivalent to a design life of 150 years.





(Fatigue testing at Delft University of Technology, Netherlands)

# Resistance to Impact

In infrastructure applications, not only is the loading distribution as prescribed by design codes, but also the resistance to impacts as well.


To demonstrate the resilience of InfraCore® Inside against impacts, panels were subjected to a mass in free fall at the laboratories of TNO. The test showed FRP's significant strain-capacity, as the applied mass bounced back.

Images made with high-speed camera show no panel failure but an elastic response instead.



# Built in Safety

In isolation glass fibers show a linear elastic behavior until failure. However when constructed together as a multi-directional laminate through the infusion method, failure behaviour is gradual and the fibers fail one by one, rather than all at the same time. Also, fibers in cross direction will be virtually unaffected by failure in the span direction. For this reason, the bespoke fiber layout of infusion is the key to safe FRP structures.







# Thermal Behaviour

InfraCore® Inside is normally based on glass fibers and a polyester resin. These materials are subject to thermal movement like most other materials, but the magnitude varies with the orientation and proportion of the fibers.

Typical values for the coefficient of thermal expansion are:

- Span direction:  $7 \times 10^{-6}/K$
- Transverse direction:  $50 \times 10^{-6}/K$

Since the coefficient of thermal expansion can be tweaked, it can be matched with that of steel ( $12 \times 10^{-6}/K$ ), which enables integrally connected hybrid structure with minimal build-up of thermal stresses. It is worthwhile noting that in case carbon fibers are used, the thermal expansion is near zero.

# Fire



In case FRP or InfraCore® Inside are set on fire, the resin will char but flames are self-extinguished as soon as the external heat source is taken away.

The structural fibers are resistant to very high temperatures and will withstand fire without any adverse effect.

The material's response to fire can be optimised with additives that release water from within the material. Local damage as a result of fire can be repaired by re-infusion.



# Climate

The structural fibers inside FRP are based on silicon (effectively sand) and are fully resistant to both high and low temperatures.

InfraCore® Inside has been exposed to liquid nitrogen (-1960<sup>°</sup>), and has come out of the test fully functional.

In hot climates, exposure to temperatures over 90<sup>°</sup> should be avoided. In areas of long term heat exposure a layer of asphalt can be applied to protect assets long term.





# Sustainability

Due to the low dead load, almost zero maintenance, long design life and the ability to recycle and regain the embodied energy after use, FRP structures have very positive sustainability credentials. Comparisons with other materials should be performed on a case-by-case basis, and include all the project characteristics, including the foundations, maintenance and after-use.

Sustainability is a very broad subject and depending on the location and the client's ambition, the following positive contributions could be considered:

- Reduced noise emissions during construction and in-use;
- Fast construction, shorter disruption, less detours being made by ongoing traffic;
- Less and lighter movements by transportation and crane-operations.

# Weights

## Examples of Structure Weights:

Length [m]	Width [m]	Deck Depth [mm]	Weight [kg]
5.0	1.2	100	508,02
7.5	1.2	100	812.84
10.0	1.2	220	1117.65
12.5	1.2	370	1625.67
15.0	1.2	510	2032.09
5.0	2.2	100	1016.04
7.5	2.2	120	1524.07
10.0	2.2	180	2133.70
12.5	2.2	270	2946.54
15.0	2.2	370	3759.37

## Design Criteria for Weights Above:

- Design load: 5kN/m<sup>2</sup> + 8ton axle load
- Deflection criteria: L/100
- Load natural frequency >2,3 Hz (TC3 0,5 P/m<sup>2</sup>);
- Max. weight railing: 50kg/m<sup>1</sup>

Weights are an indication and includes the mass of the deck including a wear surface.



# Transport, Shipping & Lifting




# Containerised Freight

Bridge elements from 2m to 30m can be shipped globally by SIS efficiently and cost effectively using our world wide transport partners, either inside containers or top loaded, via road, sea, rail or if required air.



Bridge elements can be stacked to reduce shipping costs



# Split Bridges


To ensure cost effective shipping and transport, InfraCore® bridge elements wider than 2.4m can be manufactured in parts, allowing for 2, 3 or 4 elements to become 1. This inventive step is ground breaking in it's ability to enable wide structures to be delivered to site using standard transport options and therefore dramatically reducing costs normally associated with moving wide structures.

See drawings following on how this is achieved

Photographs below show a bridge delivered to site in 2 sections, bolted together and then installed








Split bridges once bolted together have a rubber compound applied to the joint. This can be colour matched and aggregate matched to provide a seamless appearance







Top view



SECTION A-A


InfraCore deck panels, each with  
protruding horizontal & vertical flange

Rubber sealant

Wear surface

Tightly fitting bolts

3D Impression



#### Information:

1. Limited capacity for concentrated loadings
2. No transfer of bending moments

### Bolted flange connection Type - 05A

**InfraCore** inside **FiberCore** europa

Overlaid: 25. 3077 CP Rotterdam, The Netherlands +31 (0)10 475 58 58  
info@infacore.europa.com, www.infacore.europa.com

Client: FiberCore Europe

Alternative: Concrete Corridor Type - 05A

Drawing number: 0005A-0.00.00-TEK-01-C\_Bolted\_Flange Rev. 1.0

DETAIL B

SCALE 1 : 5

Drawn	Checked	Approved	Sheet
Name: K. Stoutenbeek	M. Veldkamp		1 of 1
Date: 26-1-2016	26-1-2016		Scale: 1:50
			Format: A3
			Units: mm

© copyright InfraCore Europa BV. This document is the property of InfraCore Europa BV and may contain confidential information. It is not to be distributed, copied, reproduced or in any way made use of without prior written agreement of InfraCore Europa BV.

# Lifting


A large, rectangular bridge element is being lifted by a crane. The element is suspended by a yellow lifting device and is being moved over a city street. In the background, there are historic buildings and a church spire. The sky is overcast.

Each FiberCore bridge element is designed and engineered for its own unique application.


All elements ordered come with a lifting / slinging drawing and instructions on how to best lift and install each element.

See next page for example.






Side view



DETAIL B  
SCALE 1 : 10



SECTION A-A  
SCALE 1 : 20

#### Information:

Weight deck: 8.6 Tonnes including wear surface  
Alternatively: use a lifting frame

Distance in mm	Tolerance in mm
0-50	+/- 2
50-500	+/- 5
500-5000	+/- 10
>5000	+/- 20

Bridge: Purkersdorf

Subject: Lifting Instructions

drawn to show the position of the reinforced pole




Ossele 25, 3077 CP Rotterdam, The Netherlands, +31 (0)18 479 58 58  
info@fibercore-europe.com, www.fibercore-europe.com


Client: 11-272, Purkersdorf  
Projectcode: 11-272-03-11-164-01-Lifting Instructions  
Drawing number: 11-272-03-11-164-01-Lifting Instructions  
Rev: 1.0

Drawn	Checked	Approved	Sheet	1 of 1
Name: K. Soudan	M. Veldkamp		Scale: 1:100	
Date: 21-5-2017	21-5-2017		Formal: A3	
			Units: mm	


Copyright FiberCore Europe BV. This document is the property of FiberCore Europe BV. All rights reserved. No part of this document may be reproduced or transmitted in any form or by any means electronic or mechanical, including photocopying and recording, or by any information storage or retrieval system, without prior written permission of FiberCore Europe BV.



Side view



DETAIL B  
SCALE 1 : 10



SECTION A-A  
SCALE 1 : 20

#### Information:

Weight deck: 8.6 Tonnes including wear surface  
Alternatively: use a lifting frame

Distance in mm	Tolerance in mm
0-50	+/- 2
50-500	+/- 5
500-5000	+/- 10
>5000	+/- 20

Bridge: Purkersdorf

Subject: Lifting Instructions

drawn to show the position of the reinforced pole



Ossele 25, 3077 CP Rotterdam, The Netherlands, +31 (0)18 479 59 50  
info@fibercore-europe.com, www.fibercore-europe.com

Client: 11-272, Purkersdorf  
Projectcode: 11-272-03-11-164-01-Lifting Instructions  
Drawing number: 11-272-03-11-164-01-Lifting Instructions  
Rev: 1.0

Drawn	Checked	Approved	Sheet	1 of 1
Name: K. Soudan	M. Veldkamp		Scale: 1:100	
Date: 21-5-2017	21-5-2017		Formal: A3	
			Units: mm	

Copyright FiberCore Europe BV. This document is the property of FiberCore Europe BV. All rights reserved. No part of this document may be reproduced or transmitted in any form or by any means electronic or mechanical, including photocopying and recording, or by any information storage or retrieval system, without prior written permission of FiberCore Europe BV.

# Handrail Systems


FiberCore can create a unique handrail design which is as individual and bespoke as your project.

A full range of standard handrail designs are also available.

Each project has a handrail design drawing specific to its design


See next page for example.





# Engineering Case Study

## Staines Moore Bridge United Kingdom



SECTION A-A  
SCALE 1 : 20

## Table of content

	Page
1. Introduction	3
2. Design principle and geometry of the deck	4
3. Construction principle: InfraCore Inside	5
4. Laminate- & mechanical properties of the cross-section	6
5. Actions, combinations of actions & partial factors	7
5.1 Actions	7
5.2 Combinations of actions	7
5.3 Partial factors	8
6 Thermal behaviour	9
7. Check on serviceability, SLS	10
7.1 Eigenfrequency & Accelerations	10
7.2 Deformations	10
7.3 Camber & Gradient	10
8. Check on safety, ULS	11
8.1 Strength of the skins	11
8.2 Strength of the webs	11
8.3 Strength of the fixation of the railing	12
8.4 Strength of the flanges	13
8.5 Strength of the fixation of the bridge	15
8.6 Strength of the support flanges	15
9. Actions on abutments	17
10. Conclusion	18
Corresponding drawings	
- 17-293-SM-010-TKK-1-Deck_R1.0	

Rev	Status	Date	Author	Track changes
1.0	Final	13-12-2017	FZ	Initial version



## 1. Introduction

This report describes the construction of the new InfraCore Inside pedestrian bridge in Staines, England, designed and built by FiberCore Europe (Rotterdam, The Netherlands) commissioned by ECS Engineering Services.

This bridge has a length of  $L_{rd} = 6.1 \text{ m}$  and a width of  $B_{tot} = 1.50 \text{ m}$ .

The InfraCore Inside bridge is an integral structure made from fiber-reinforced polymers (FRP), more specifically glassfibers in combination with a polyester matrix (glassfiber reinforced polyester or GFRP). The glassfibers carry the loads acting on the bridge, the matrix supports the fibers, transfers loads between fibers and gives the bridge its shape.

GFRP has a high specific strength (strength vs specific weight), resulting in relatively lightweight structures (bridges) capable of carrying large loads with high margins of safety.

The bridge has been designed according to Eurocodes, including British national annexes, and CUR-recommendation 96.

FiberCore Europe is responsible for the engineering and manufacturing of the composite bridge.

## 2. Design principles and geometry of the decks

The InfraCore Inside decks are designed in compliance with the following relevant standards:


- EN 1990+A1+A1/C2:2011, "Eurocode 0: Basis of structural design"
  - EN 1991-2+C1:2011, "Eurocode 1: Actions on structures - Part 2: Traffic loads on bridges"
  - EN 1991-1-5+C1:2011, "Eurocode 1: Actions on structures - Part 5: General actions - Thermal actions"
  - [EUR23984] "Design of Lightweight Foot-Bridges for Human Induced Vibrations"
  - [CUR-recommendation 96:2003] "Fibre reinforced plastics in civil engineering supporting frameworks"
- 
- Technical design life            100yr
  - Consequence class                CC1
  - Traffic class                        TC3

The main parameters describing the design of the considered deck are given below. For more details on the geometry of the decks, refer to the accompanying drawing.

Total length	$L_{\text{tot}} = 6.1 \cdot \text{m}$
Length of deck	$L_{\text{rd}} = 6.1 \cdot \text{m}$
Span	$L_{\text{o}} = 5.7 \cdot \text{m}$
Width	$B_{\text{tot}} = 1.5 \text{ m}$
Effective width (between railings)	$B_{\text{eff}} = 1.2 \text{ m}$
Construction height	$H_{\text{b}} = 140 \cdot \text{mm}$
Width flange	$B_{\text{fh}} = 200 \cdot \text{mm}$
Total surface area	$A_{\text{bridge}} = 9.1 \text{ m}^2$
Total mass	$M_{\text{tot}} = 1.2 \times 10^3 \cdot \text{kg}$
Assumed mass of the railing per meter	$M_{\text{L.rail}} = 50 \text{ kg} \cdot \text{m}^{-1}$

The bridge is assumed to be simply supported on the two abutments beneath the two bulkheads. Both abutments are acting as line supports for the bridge where all webs are supported such that the loads are transferred from the webs through the bulkheads into the abutments.

The bridge will be fixed in longitudinal and transverse direction at one abutment. The bridge will be fixed in transverse direction and will be free to move in longitudinal direction and at the second abutment to accommodate the thermal expansion. The fixation is done with threaded rods through the bottom of the bridge.




### 3. Construction principle: InfraCore Inside

The bridge is produced as an InfraCore Inside structure (ICI). An ICI structure can be described as a sandwich structure with two FRP skins at the top and bottom of the bridge, and an FRP-reinforced foam core. The core reinforcement consists of FRP shear webs in longitudinal (flat) direction of the bridge.

Skins and longitudinal shear webs are constructed from the same base materials, in this case non-crimp fabrics, running through the topskin, a shear web and the bottomskin. This ensures a durable, fiber-reinforced connection between skins and shear webs, eliminating the risk of skin-core debonding. Such a layer connecting both skins through the core are called Z-layers, after the shape of each of these layers. To add stiffness or strength, extra material can be added to the skin and/or shear webs.

The stacking sequence of fabrics results in a layered structure (a laminate), each layer called a ply.

All fibers are E-glass fibers, the matrix is a polyester resin.





## 4 Laminate- & mechanical properties of the cross-section

The applied laminates are anisotropic. The local coordinate systems of each laminate is orientated as follows:

x axis: in-plane, in span direction of the bridge  
y axis: in-plane, perpendicular to the span direction of the bridge  
z axis: out of plane, perpendicular to the laminate

Multiple different laminates, with each their own properties, are applied in the bridge. The laminate properties are calculated with standard micromechanics models and classical lamination theory as is stated in the CUR96.

The used properties used in the calculations are listed here:

Topskin	$t_{ts} = 12 \cdot \text{mm}$	$E_{x,ts} = 32 \cdot \text{GPa}$	$E_{y,ts} = 19 \cdot \text{GPa}$	
	$\sigma_{x,ts} = 386 \cdot \text{MPa}$	$\sigma_{y,ts} = 226 \cdot \text{MPa}$	$\tau_{xy,ts} = 98 \cdot \text{MPa}$	
Bottomskin	$t_{bs} = 12 \cdot \text{mm}$	$E_{x,bs} = 34 \cdot \text{GPa}$	$E_{y,bs} = 17 \cdot \text{GPa}$	
	$\sigma_{x,bs} = 413 \cdot \text{MPa}$	$\sigma_{y,bs} = 199 \cdot \text{MPa}$	$\tau_{xy,bs} = 98 \cdot \text{MPa}$	
Flange	$t_f = 20 \cdot \text{mm}$	$E_{x,f} = 26 \cdot \text{GPa}$	$E_{y,f} = 26 \cdot \text{GPa}$	$G_{xy,f} = 6 \cdot \text{GPa}$
	$\sigma_{x,f} = 306 \cdot \text{MPa}$	$\sigma_{y,f} = 306 \cdot \text{MPa}$	$\tau_{xy,f} = 98 \cdot \text{MPa}$	$\tau_{yz,f} = 39 \cdot \text{MPa}$
Edge	$t_e = 13 \cdot \text{mm}$	$E_{x,e} = 26 \cdot \text{GPa}$	$E_{y,e} = 26 \cdot \text{GPa}$	$G_{xy,e} = 6 \cdot \text{GPa}$
	$\sigma_{x,e} = 306 \cdot \text{MPa}$	$\sigma_{y,e} = 306 \cdot \text{MPa}$	$\tau_{xy,e} = 98 \cdot \text{MPa}$	
Webs	$t_w = 5 \cdot \text{mm}$	$E_{x,w} = 12 \cdot \text{GPa}$	$E_{y,w} = 12 \cdot \text{GPa}$	$G_{xy,w} = 4 \cdot \text{GPa}$
	$\sigma_{x,w} = 143 \cdot \text{MPa}$	$\sigma_{y,w} = 143 \cdot \text{MPa}$	$\tau_{xy,w} = 64 \cdot \text{MPa}$	
Support flange	$t_{sf} = 10 \cdot \text{mm}$	$E_{x,sf} = 26 \cdot \text{GPa}$	$E_{y,sf} = 26 \cdot \text{GPa}$	$G_{xy,sf} = 6 \cdot \text{GPa}$
	$\sigma_{x,sf} = 306 \cdot \text{MPa}$	$\sigma_{y,sf} = 306 \cdot \text{MPa}$	$\tau_{xy,sf} = 98 \cdot \text{MPa}$	


The normal, bending and shear stiffness of the bridge are calculated by the summation of the property of each independent laminate. Only the webs and edges taken into account in the calculation of the shear stiffness.

$$EA_x = 1.2 \times 10^9 \cdot \text{N} \quad EI_{yy} = 4 \cdot \text{MN} \cdot \text{m}^2 \quad GA_{xz} = 3.1 \times 10^7 \cdot \text{N}$$

The thermal behaviour of the bridge is dominated by the skins. The thermal expansion coefficient of the top and bottomskins can vary a bit from each other due to a small difference in lay-up. The average thermal expansion coefficient of both skins is taken to determine the thermal behaviour of the bridge.

$$\alpha_x = 11.6 \times 10^{-6} \cdot \text{K}^{-1} \quad \alpha_y = 19.5 \times 10^{-6} \cdot \text{K}^{-1}$$

Cross-section of the construction



## 5 Actions, combination of actions & partial factors

### 5.1 Actions

#### Permanent loads

The permanent load on the bridge is its self-weight of the structural and non-structural members. The structural member is the InfraCore Inside GFRP bridge deck. The non structural members are the wear surface and railings.

$$\text{Total self-weight as distributed load} \quad q_m = M_{\text{tot}} \cdot g \cdot A_{\text{bridge}}^{-1} = 1.3 \cdot \text{kN} \cdot \text{m}^{-2}$$

#### Live loads

The normative live loads that are taken into account are given below. Live loads, like wind and snow loads, not mentioned are assumed to be not normative and therefore not taken into account in the design. This assumption is based on the combination rules and combination factors listed in EN1990.

$$\text{Uniform distributed load [EC-1]} \quad q_{fk} = 5 \cdot \text{kN} \cdot \text{m}^{-2}$$

$$\begin{aligned} \text{Concentrated load [EC-1]} \\ \text{Load} \quad Q_{fwb} &= 10 \cdot \text{kN} \\ \text{Acting on square surface with sides} \quad B_{fwb} &= 0.1 \cdot \text{m} \end{aligned}$$

$$\begin{aligned} \text{Horizontal load [EC-1]} \\ \text{Due to uniform distributed load} \quad Q_{fk,q} &= 4 \cdot \text{kN} \end{aligned}$$

$$\begin{aligned} \text{Dense crowd for dynamic response [EUR23984]} \\ \text{Mass of one person} \quad P_1 &= 800 \text{ N} \\ \text{Density crowd} \quad d_{TC} &= 0.5 \cdot P_1 \cdot \text{m}^{-2} \end{aligned}$$

$$\begin{aligned} \text{Load on railings [EC-1]} \\ \text{Line load on top of railing} \quad q_{lk} &= 1.0 \cdot \text{kN} \cdot \text{m}^{-1} \end{aligned}$$

#### Accidental loads

There are no accidental loads taken into account for this bridge.

### 5.2 Combination of actions

The combinations of actions on this bridge are based on formula 6.10b EN1990 6.4.3.2 and the tables in EN1990, A2.2.6 and are listed below. The design of the bridge is dominated by its serviceability (stiffness) when loaded with the live loads. All load combinations are used to check the safety (strength) of the bridge.

LC =	"-"	"LC0"	"LC1"	"LC3"
	"Load"	"EG"	"gr1"	"Qfwb"
	"q.EG"	1	1	1
	"q.fk"	0	1	0
	"Q.fk,q"	0	1	0
	"Q.fwb"	0	0	1

### 5.3 Partial factors

The used partial factors are given in the Eurocode and CUR-recommendation 96. The consequence class of this bridge is defined as CC1 (  $K_{FI} = 0.9$  ). The CUR defines different conversion factors to take into account the effect on the material properties of different sources. Which conversion factors are taken into account are depending on the situation and type of load.

Material factors	Scatter in material properties		$\gamma_{m1} = 1.35$
	Production proces		$\gamma_{m2} = 1.20$
Conversion factors	Temperature (t)		$\gamma_{ct} = 1.10$
	Moisture (v)		$\gamma_{cv} = 1.10$
	Fatigue (f)		$\gamma_{cf} = 1.10$
	Creep (k)		$\gamma_{ck} = 1.24$
Factors for the service limit state (SLS)			
Load factor			$\gamma_f = 1.00$
Material factor			$\gamma_{m.SLS} = 1.00$
Conversion factors	Vibrations	Permanent loads (t,v,f)	$\gamma_{cv.p} = 1.33$
		Live loads (t,v)	$\gamma_{cv.l} = 1.21$
	Deformations	Permanent loads (t,v,f,k)	$\gamma_{cd.p} = 1.65$
		Live loads (t,v,f)	$\gamma_{cd.l} = 1.21$
Factors for the ultimate limit state (ULS)			
Load factors	Permanent loads		$\gamma_G = 0.89 \cdot 1.35 \cdot K_{FI} = 1.08$
	If favorable		$\gamma_{G.inf} = 0.89 \cdot 1.0 = 0.89$
	Live loads		$\gamma_Q = 1.35 \cdot K_{FI} = 1.22$
Material factors(m1, m2)			$\gamma_{m.ULS} = 1.62$
Conversion factors	Strength	Permanent loads (t,v,k)	$\gamma_{cs.p} = 1.50$
		Live loads (t,v)	$\gamma_{cs.l} = 1.21$
Additional reductionfactor due to the productionproces (ULS)			
Topskin			$\gamma_{ts} = 1.18$
Bottomskin			$\gamma_{bs} = 1.12$
Webs			$\gamma_w = 1.47$

Some fibers/layers are locally interrupted in the construction due to the production proces. These interruptions, which are very locally, are resulting in local weaker spots in the construction. The additional reduction factors are taken into account for the ULS (strength) to compensate the interruption of the fibers. These interruptions have no significant influence on the stiffness of the bridge. Therefore they are not taken into account in the SLS.



## 6 Thermal behaviour of the bridge

Due to changes in temperature the bridge deck will contract/expand in longitudinal and transverse direction. The temperature components are derived from the EN 1991-1-5+C1:2011. This design is more of type 1 than any of the other types.

Design temperature	$T_0 = 10 \cdot ^\circ\text{C}$
Minimal temperature in the shadow	$T_{\min} = -18 \cdot ^\circ\text{C}$
Maximum temperature in the shadow	$T_{\max} = 34 \cdot ^\circ\text{C}$
Temperature difference between shadow - bridge	$\Delta T_{e,\min} = -3 \cdot ^\circ\text{C}$ $\Delta T_{e,\max} = 16 \cdot ^\circ\text{C}$
Temperature difference component	$\Delta T_{M,\text{heat}} = 30 \cdot ^\circ\text{C}$ $\Delta T_{M,\text{cool}} = 8 \cdot ^\circ\text{C}$
Additional temperature difference for expansion joints	$\Delta T_{\text{dil}} = 20 \cdot ^\circ\text{C}$
Combination factors	$\omega_N = 0.35$ $\omega_M = 0.75$
Uniform temperature component bridge	$T_{e,\min} = T_{\min} + \Delta T_{e,\min} = -21 \cdot ^\circ\text{C}$ $T_{e,\max} = T_{\max} + \Delta T_{e,\max} = 50 \cdot ^\circ\text{C}$ $\Delta T_N = T_{e,\max} - T_{e,\min} = 71 \cdot ^\circ\text{C}$
Maximum temperature change contraction	$\Delta T_{N,\text{con}} = T_0 - T_{e,\min} = 31 \cdot ^\circ\text{C}$
Maximum temperature change expansion	$\Delta T_{N,\text{exp}} = T_{e,\max} - T_0 = 40 \cdot ^\circ\text{C}$

Normative temperature combination for the bridge and expansion joints

$$\begin{aligned}\Delta T_{\text{exp}} &= \max(\Delta T_{M,\text{heat}} + \omega_N \cdot \Delta T_{N,\text{exp}}, \omega_M \cdot \Delta T_{M,\text{heat}} + \Delta T_{N,\text{exp}}) = 63 \cdot ^\circ\text{C} \\ \Delta T_{\text{con}} &= \max(\Delta T_{M,\text{cool}} + \omega_N \cdot \Delta T_{N,\text{con}}, \omega_M \cdot \Delta T_{M,\text{cool}} + \Delta T_{N,\text{con}}) = 37 \cdot ^\circ\text{C} \\ \Delta T_{d,e} &= \max[\Delta T_{M,\text{heat}} + \omega_N \cdot (\Delta T_{N,\text{exp}} + \Delta T_{\text{dil}}), \omega_M \cdot \Delta T_{M,\text{heat}} + (\Delta T_{N,\text{exp}} + \Delta T_{\text{dil}})] = 83 \cdot ^\circ\text{C} \\ \Delta T_{d,c} &= \max[\Delta T_{M,\text{cool}} + \omega_N \cdot (\Delta T_{N,\text{con}} + \Delta T_{\text{dil}}), \omega_M \cdot \Delta T_{M,\text{cool}} + (\Delta T_{N,\text{con}} + \Delta T_{\text{dil}})] = 57 \cdot ^\circ\text{C}\end{aligned}$$

Maximum expansion/contraction due to the normative temperature components

Bridge	Total expansion joints
$\Delta L_{\text{dek.exp}} = \Delta T_{\text{exp}} \cdot \alpha_x \cdot L_{\text{rd}} = 4.4 \cdot \text{mm}$	$\Delta L_{\text{dil.exp}} = \Delta T_{d,e} \cdot \alpha_x \cdot L_{\text{rd}} = 5.8 \cdot \text{mm}$
$\Delta L_{\text{dek.con}} = \Delta T_{\text{con}} \cdot \alpha_x \cdot L_{\text{rd}} = 2.6 \cdot \text{mm}$	$\Delta L_{\text{dil.con}} = \Delta T_{d,c} \cdot \alpha_x \cdot L_{\text{rd}} = 4.0 \cdot \text{mm}$
$\Delta B_{\text{dek.exp}} = \Delta T_{\text{exp}} \cdot \alpha_y \cdot B_{\text{tot}} = 1.8 \cdot \text{mm}$	$\Delta B_{\text{dil.exp}} = \Delta T_{d,e} \cdot \alpha_y \cdot B_{\text{tot}} = 2.4 \cdot \text{mm}$
$\Delta B_{\text{dek.con}} = \Delta T_{\text{con}} \cdot \alpha_y \cdot B_{\text{tot}} = 1.1 \cdot \text{mm}$	$\Delta B_{\text{dil.con}} = \Delta T_{d,c} \cdot \alpha_y \cdot B_{\text{tot}} = 1.7 \cdot \text{mm}$

The fixation of the bridge with one foundation has slotted holes such that the bridge can freely expand/contract. Therefore, there will be no significant thermal stresses in the construction.

## 7 Check on serviceability, SLS

The following design requirements are applicable to the design in order to ensure that the use of the bridge is comfortable.

- Minimum eigenfrequency of 3.0 Hz when unloaded
- Minimum eigenfrequency of 2.3 Hz when loaded with the dense crowd
- Maximum deflection of  $\delta_{all} = \frac{L_0}{100} = 57 \cdot \text{mm}$  under live loads
- Maximum gradient of  $\varphi_{max} = 4.0\%$  to ensure easy and good accessibility
- Average gradient of minimal  $\varphi_{avg} = 0.5\%$  to ensure good drainage of the bridge

### 7.1 Eigenfrequency

The bridge is modelled as a simply supported beam. The first eigenfrequency of a simply supported beam is calculated with:

$$f(K, d_{TC}) = \frac{K}{2\pi} \cdot \sqrt{\frac{EI_{yy} \cdot g \cdot \gamma_{m.SLS}^{-1}}{(\gamma_{cv.p} \cdot q_m \cdot B_{tot} + \gamma_{cv.l} \cdot d_{TC} \cdot B_{eff}) \cdot L_0^4}}$$

Where constant  $K_{ss,0} = 9.87$  and dependent on the boundary conditions and which eigenfrequency is evaluated. In previous research it is concluded that the calculated eigenfrequency can increased with 18% due to the fact that the support conditions in reality are not fully simply supported. This 18% is determined with a confidence level of 95%.

First eigenfrequency, unloaded bridge  $f_{0.unloaded} = f(1.18 \cdot K_{ss,0}, 0) = 7.3 \cdot \text{Hz}$

First eigenfrequency, loaded bridge  $f_{0.loaded} = f(1.18 \cdot K_{ss,0}, d_{TC}) = 6.6 \cdot \text{Hz}$

The eigenfrequencies are high enough to avoid uncomfortable accelerations.

### 7.2 Deformations

The deformations due to the live loads are calculated with the beam theory.

Deformation load combination 1, uniform distributed load

$$\delta_{LC1} = \frac{5}{384} \cdot \frac{q_{fk} \cdot B_{eff} \cdot L_0^4}{EI_{yy}} + \frac{1}{8} \cdot \frac{q_{fk} \cdot B_{eff} \cdot L_0^2}{GA_{xz}} = 20 \cdot \text{mm}$$

$$\delta_{LC1.k} = \gamma_f \cdot \gamma_{m.SLS} \cdot \gamma_{cd.l} \cdot \delta_{LC1} = 24 \cdot \text{mm}$$

Unity checks  $uc_{\delta.LC1} = \frac{\delta_{LC1.k}}{\delta_{all}} = 0.42$

### 7.3 Camber & Gradient

The bridge is produced with a constant radius. The camber maximum and average gradient during production, begin design life (self weight taken into account) and end design life (creep and material degradation taken into account) are:

Bulge <sub>p</sub> = 39 · mm	Bulge <sub>i</sub> = 32 · mm	Bulge <sub>e</sub> = 28 · mm
$\varphi_{max.p} = 2.5 \cdot \%$	$\varphi_{max.i} = 2.1 \cdot \%$	$\varphi_{max.e} = 1.8 \cdot \%$
$\varphi_{avg.p} = 1.3 \cdot \%$	$\varphi_{avg.i} = 1.1 \cdot \%$	$\varphi_{avg.e} = 0.9 \cdot \%$

The maximum and average gradient are satisfying the requirements for the accessibility and drainage of the bridge.

## 8 Check on safety (ULS)

The laminates of the skins, webs and flanges are checked on their strengths for the most critical load combinations. the fixation of the railings and of the bridge to the foundations are also checked on their strength.

### 8.1 Strength of the skins

The strength of the skins is checked for load combination 1.

Maximum bending moments

Self weight

$$M_m = \frac{1}{8} \cdot q_m \cdot B_{\text{tot}} \cdot L_o^2 = 8 \cdot \text{kN} \cdot \text{m}$$

Uniform distributed load

$$M_q = \frac{1}{8} \cdot q_{fk} \cdot B_{\text{tot}} \cdot L_o^2 = 30 \cdot \text{kN} \cdot \text{m}$$

Per load combination

$$M_{LC1} = \gamma_m \cdot UGT \cdot (\gamma_G \cdot \gamma_{cs,p} \cdot M_m + \gamma_Q \cdot \gamma_{cs,l} \cdot M_q) = 93 \cdot \text{kN} \cdot \text{m}$$

Stress in the skins

Distance of topskin to neutralline

$$z_{ts} = 61 \cdot \text{mm}$$

Distance of bottomskin to neutralline

$$z_{bs} = -79 \cdot \text{mm}$$

Second moment of inertia of the skins

$$I_h = 1.1 \times 10^8 \cdot \text{mm}^4$$

Stress in topskin

$$\sigma_{ts,x,M} = \frac{\gamma_{ts} \cdot M_{LC1} \cdot z_{ts}}{I_h} = 61 \cdot \text{MPa}$$

Stress in bottomskin

$$\sigma_{bs,x,M} = \frac{\gamma_{bs} \cdot M_{LC1} \cdot z_{bs}}{I_h} = -76 \cdot \text{MPa}$$

Allowable stress in the skins

Topskin

$$\sigma_{x,ts} = 386 \cdot \text{MPa}$$

Bottomskin

$$\sigma_{x,bs} = 413 \cdot \text{MPa}$$

Unity checks

$$uc_{ts,\sigma} = \frac{|\sigma_{ts,x,M}|}{\sigma_{x,ts}} = 0.16$$

$$uc_{bs,\sigma} = \frac{|\sigma_{bs,x,M}|}{\sigma_{x,bs}} = 0.18$$

### 8.2 Strength of the webs

The strength of the webs is checked on shear for load combination 1 and 3 and on compression for load combination 3.

All the webs are considered to be the thin web of a I-beam with thick flanges. The shear stress is calculated with  $\tau = \frac{V}{A}$

where A is the cross-sectional area of the web. The height of the webs are taken as the distance between the two centroids of the top and bottomskins. the center-to-center distance of the webs is  $c_{c_w} = 210 \cdot \text{mm}$

Maximum shear force one web

Self weight

$$V_m = \frac{1}{2} q_m \cdot c_{c_w} \cdot L_o = 0.8 \cdot \text{kN}$$

Uniform distributed load

$$V_q = \frac{1}{2} q_{fk} \cdot c_{c_w} \cdot L_o = 3.0 \cdot \text{kN}$$

Concentrated load

$$V_{fwk} = Q_{fwk} = 10.0 \cdot \text{kN}$$

Per load combination

$$V_{LC1} = \gamma_w \cdot \gamma_m \cdot UGT \cdot (\gamma_G \cdot \gamma_{cs,p} \cdot V_m + \gamma_Q \cdot \gamma_{cs,l} \cdot V_q) = 14 \cdot \text{kN}$$

$$V_{LC3} = \gamma_w \cdot \gamma_m \cdot UGT \cdot (\gamma_G \cdot \gamma_{cs,p} \cdot V_m + \gamma_Q \cdot \gamma_{cs,l} \cdot V_{fwk}) = 38 \cdot \text{kN}$$



Shearstress in web

$$\text{Cross-section area of one web} \quad A_w = t_w \cdot \left( H_b - \frac{t_{ts} + t_{bs}}{2} \right) = 644 \cdot \text{mm}^2$$

$$\text{Shear stress} \quad \tau_{w.xy,V} = \max(V_{LC1}, V_{LC3}) \cdot A_w^{-1} = 59 \cdot \text{MPa}$$

$$\text{Allowable shear stress} \quad \tau_{xy,w} = 64 \cdot \text{MPa}$$

$$\text{Unity check} \quad u_{c_{w,\tau}} = \frac{\tau_{w.xy,V}}{\tau_{xy,w}} = 0.93$$

The maximum compression stress in one web occurs when the concentrated load is placed directly above the web and is calculated with  $\sigma = \frac{P}{A}$ .

The maximum compression force on one web (load and material factors included):

$$P_{LC3} = \gamma_{m,ULS} \cdot (\gamma_{cs,p} \cdot \gamma_G \cdot q_m \cdot c_{c,w} \cdot B_{fwk} + \gamma_{cs,l} \cdot \gamma_Q \cdot Q_{fwk}) = 24 \cdot \text{kN}$$

$$\text{The maximum compression stress in one web: } \sigma_{w,max} = \frac{P_{LC3}}{B_{fwk} \cdot t_w} = 47 \cdot \text{MPa}$$

$$\text{Design strength of the web} \quad \sigma_{y,w} = 143 \cdot \text{MPa}$$

$$\text{Unity check} \quad u_{c_{w,\sigma}} = \frac{\sigma_{w,max}}{\sigma_{y,w}} = 0.33$$

### 8.3 Strength of the fixation of the railing

It is assumed that the railings are fixed to the flange with 2 pairs of bolts. The strength of the bolts is checked on the situation that the railing is loaded with the line load on the top rail.

Height of the railing	$H_{rail} = 1.2 \text{ m}$
Spacing stanchion	$s_{stan} = 1.5 \text{ m}$
Diameter bolt, metric	$d_{b,l} = 12 \cdot \text{mm}$
class of the bolt	$klasse_{b,l} = 8.8$

c-c distance bolts	x direction	$c_{c,x,b} = 120 \cdot \text{mm}$
	y direction	$c_{c,y,b} = 80 \cdot \text{mm}$

Edge distance bolt - baseplate	x direction	$e_{x,base} = 30 \cdot \text{mm}$
	y direction	$e_{y,base} = 30 \cdot \text{mm}$

Edge distance bolt - edge laminate	$e_{y,b} = 50 \cdot \text{mm}$
------------------------------------	--------------------------------

Load on one bolt

$$\text{Tensile} \quad F_{t,b} = \frac{\gamma_{Q1} \cdot q_{lk} \cdot s_{stan} \cdot H_{rail}}{2 \cdot \left( \frac{e_{y,base}^2}{e_{y,base} + c_{c,y,b}} + e_{y,base} + c_{c,y,b} \right)} = 9 \cdot \text{kN}$$

$$\text{Shear} \quad F_{v,b} = \frac{1}{4} (\gamma_{Q1} \cdot q_{lk} \cdot s_{stan}) = 0.5 \cdot \text{kN}$$

Allowable load on one bolt

Tensile  $F_{t.b.alw} = 49 \cdot \text{kN}$

Shear  $F_{v.b.alw} = 27 \cdot \text{kN}$

Unity check 
$$uc_{b,l} = \left( \frac{F_{t,b}}{F_{t,b.alw}} + \frac{F_{v,b}}{F_{v,b.alw}} + \frac{F_{v,b}}{F_{v,b.alw}} + \frac{F_{t,b}}{1.4F_{t,b.alw}} \right) = (0.19 \quad 0.02 \quad 0.15)$$

## 8.4 Strength of the flanges

The strength of the flanges is checked around the connections of the standhions

Diameter hole  $d_{g,l} = 14 \cdot \text{mm}$

Diameter washer  $d_{r,l} = 40 \cdot \text{mm}$

### Laminate around the holes for the bolts

Allowable stress in y direction 
$$\sigma_{y,f.alw} = \frac{\sigma_{y,f}}{\gamma_{m,ULS} \cdot \gamma_{cs,l}} = 156 \cdot \text{MPa}$$

Allowable shear stress in xy plane 
$$\tau_{xy,f.alw} = \frac{\tau_{xy,f}}{\gamma_{m,ULS} \cdot \gamma_{cs,l}} = 50 \cdot \text{MPa}$$

Allowable shear stress in yz plane 
$$\tau_{yz,f.alw} = \frac{\tau_{yz,f}}{\gamma_{m,ULS} \cdot \gamma_{cs,l}} = 20 \cdot \text{MPa}$$

Compressive stresses

Stress concentration factor 
$$K_c = \left( \frac{d_{g,l}}{d_{b,l}} \right)^2 = 1.36$$

Compressive stress 
$$\sigma_{f,b,y,c} = \frac{F_{v,b} \cdot K_c}{d_{g,l} \cdot t_f} = 2.2 \cdot \text{MPa}$$

Unity check

$$uc_{f,b,\sigma yc} = \frac{\sigma_{f,b,y,c}}{\sigma_{y,f.alw}} = 0.01$$

Tensile stresses

The tensile stresses around the holes are calculated according to the theory published in "Peterson's stress concentration factors" author Walter D. Pilkey and Deborah F. Pilkey, 2008. The graph used to determine the stress concentration factor is republished in the figure below

Ratio diameter hole - c\_c distance holes 
$$r_{g,b,l} = \frac{d_{g,l}}{c_{x,b}} = 0.12$$

Stress concentration factor  $K_t = 8$

Tensile stress 
$$\sigma_{f,b,y,t} = \frac{K_t \cdot F_{v,b}}{(c_{x,b} - d_{g,l}) \cdot t_f} = 1.7 \cdot \text{MPa}$$

Unity check

$$uc_{f,b,\sigma yt} = \frac{\sigma_{f,b,y,t}}{\sigma_{y,f.alw}} = 0.01$$


Shear stress

$$\text{Shear stress due to shear out} \quad \tau_{f.b.xy.s} = \frac{F_{v.b}}{2 \cdot e_{y.b} \cdot t_f} = 0.2 \cdot \text{MPa}$$

$$\text{Shear stress due to pull-through} \quad \tau_{f.b.yz.p} = \frac{F_{t.b}}{\pi \cdot d_{r.l} \cdot t_f} = 3.6 \cdot \text{MPa}$$

Unity check

$$uc_{f.b.\tau yz} = \left( \frac{\tau_{f.b.xy.s}}{\tau_{xy.f.alw}} \quad \frac{\tau_{f.b.yz.p}}{\tau_{yz.f.alw}} \right) = (0.00 \quad 0.18)$$



## 8.5 Strength of the fixation of the bridge

The bridge is fixed to the two abutments with threaded rods. These rods are fitted through the holes in the support flanges which are attached to the bottomside of the bridge. In one of the flanges, the holes are slotted such that the thermal expansion or contraction of the bridge doesn't lead to thermal stresses. One function of these rods is to transfer the horizontal force to the abutments.

The threaded rods

Total number of rods	$n_d = 4$
Number of load bearing rods in x direction	$n_{d,x} = 2$
Number of load bearing rods in y direction	$n_{d,y} = 4$
Diameter rods, metric	$d_d = 24 \cdot \text{mm}$
Diameter washer	$d_{d,r} = 72 \text{mm}$
Material class	$\text{klasse}_d = 8.8$
Diameter hole	$d_{g,d} = 32 \cdot \text{mm}$
Edge laminate - hole distance	$e_{x,d} = 100 \cdot \text{mm}$

Load per rod

$$\text{Shear in x direction} \quad F_{v.x.LC1} = \frac{\gamma_Q \cdot Q_{flk.q}}{n_{d,x}} = 2 \cdot \text{kN}$$

$$\text{Shear in y direction} \quad F_{v.y.LC1} = \frac{\gamma_Q \cdot Q_{flk.q}}{n_{d,y}} = 1 \cdot \text{kN}$$

Allowable shear force on one rod

$$F_{v.d.alw} = 112 \cdot \text{kN}$$

Unity check

$$uc_d = \left( \frac{F_{v.x.LC1}}{F_{v.d.alw}} \quad \frac{F_{v.y.LC1}}{F_{v.d.alw}} \right) = (0.02 \quad 0.01)$$



## 8.6 Strength of the support flanges

The laminate around the holes for the rods is checked on strength.

Allowable stress in x direction	$\sigma_{x.s.f.alw} = \frac{\sigma_{x.s.f}}{\gamma_{m.ULS} \cdot \gamma_{cs.l}} = 156 \cdot \text{MPa}$
Allowable stress in y direction	$\sigma_{y.s.f.alw} = \frac{\sigma_{y.s.f}}{\gamma_{m.ULS} \cdot \gamma_{cs.l}} = 156 \cdot \text{MPa}$
Allowable shear stress in xy direction	$\tau_{xy.s.f.alw} = \frac{\tau_{xy.s.f}}{\gamma_{m.ULS} \cdot \gamma_{cs.l}} = 50 \cdot \text{MPa}$
Compressive stress	
Stress concentration factor	$K_c = \left( \frac{d_{g.d}}{d_d} \right)^2 = 1.78$
Compressive stress in x direction	$\sigma_{sf.x.c} = \frac{F_{v.x.LC1} \cdot K_c}{d_{g.d} \cdot t_{sf}} = 12 \cdot \text{MPa}$
Compressive stress in y direction	$\sigma_{sf.y.c} = \frac{F_{v.y.LC1} \cdot K_c}{d_{g.d} \cdot t_{sf}} = 6 \cdot \text{MPa}$
Unity check	$u_{c.s.f.\sigma c} = \left( \frac{\sigma_{sf.x.c}}{\sigma_{x.s.f.alw}} \quad \frac{\sigma_{sf.y.c}}{\sigma_{y.s.f.alw}} \right) = (0.08 \quad 0.04)$
Tensile stress	
The loaded width is limited due to the limited edge laminate - hole distance.	
Loaded width	$B_{eff.d} = d_{g.d} + 2e_{x.d} = 232 \cdot \text{mm}$
Ratio hole diameter - loaded width	$r_{g.b.d} = \frac{d_{g.d}}{B_{eff.d}} = 0.14$
Stress concentration factor	$K_t = 7$
Tensile stress in x direction	$\sigma_{sf.x.t} = \frac{K_t \cdot F_{v.x.LC1}}{(B_{eff.d} - d_{g.d}) \cdot t_{sf}} = 8 \cdot \text{MPa}$
Tensile stress in y direction	$\sigma_{sf.y.t} = \frac{K_t \cdot F_{v.y.LC1}}{(B_{eff.d} - d_{g.d}) \cdot t_{sf}} = 4 \cdot \text{MPa}$
Unity check	$u_{c.s.f.\sigma t} = \left( \frac{\sigma_{sf.x.t}}{\sigma_{x.s.f.alw}} \quad \frac{\sigma_{sf.y.t}}{\sigma_{y.s.f.alw}} \right) = (0.05 \quad 0.02)$
Shear stress	
Shear stress due to shear out	$\tau_{sf.xy.s} = \frac{\max(F_{v.x.LC1}, F_{v.y.LC1})}{2 \cdot e_{x.d} \cdot t_{sf}} = 1 \cdot \text{MPa}$
Unity check	$u_{c.s.f.\tau} = \frac{\tau_{sf.xy.s}}{\tau_{xy.s.f.alw}} = 0.02$

### Check on buoyancy

The buoyancy will be determined by calculating the buoyancy force using Archimede's principle.

The volume of water displaced by the bridge  $V_{\text{tot}} = 1.00 \cdot \text{m}^3$

Density of fresh water  $\rho_{\text{fresh.water}} = 1000 \frac{\text{kg}}{\text{m}^3}$

Buoyancy force  $F_b = V_{\text{tot}} \cdot \rho_{\text{fresh.water}} \cdot g = 9.76 \cdot \text{kN}$

Weight of the bridge  $W_b = M_{\text{tot}} \cdot g = 12.07 \cdot \text{kN}$

The bridge is heavier than an equal volume of water and therefore will not float.

## 9 Actions on the abutments

The actions on the abutments due to the permanent and live loads on the bridge are:

In vertical direction per abutment over the full width of the bridge

Permanent loads

$$F_{v,p} = \gamma_G \cdot 0.5 M_{\text{tot}} \cdot g = 7 \cdot \text{kN}$$

Live loads

$$F_{v,l} = \frac{1}{2} \cdot \gamma_Q \cdot q_{fk} \cdot B_{\text{eff}} \cdot L_o = 21 \cdot \text{kN}$$

Total

$$F_{v,\text{abutment}} = F_{v,p} + F_{v,l} = 27 \cdot \text{kN}$$

In longitudinal direction at the abutments

$$F_{h,x,\text{abutment},1} = \gamma_Q \cdot Q_{fk,q} = 4 \cdot \text{kN}$$

$$F_{h,x,\text{abutment},2} = 0 \cdot \text{kN}$$

In lateral direction per abutment

$$F_{h,y,\text{abutment}} = \frac{1}{2} \cdot \gamma_Q \cdot Q_{fk,q} = 2 \cdot \text{kN}$$



## 10 Conclusion

### SLS results

First eigenfrequency	Unloaded	$f_{0,\text{unloaded}} = 7.3 \cdot \text{Hz}$	$\geq 3.0 \text{ Hz}$
	Loaded	$f_{0,\text{loaded}} = 6.6 \cdot \text{Hz}$	$\geq 2.3 \text{ Hz}$
Deformations	LC1	$uc_{\delta,\text{LC1}} = 0.42$	$\leq 1.00$
Maximum gradient		$\varphi_{\text{max},i} = 2.1 \cdot \%$	$\leq \varphi_{\text{max}} = 4.0 \cdot \%$
Average gradient		$\varphi_{\text{avg},e} = 0.9 \cdot \%$	$\geq \varphi_{\text{avg}} = 0.5 \cdot \%$

### ULS results

Topskin	Moment	$uc_{\text{ts},\sigma} = 0.16$	$\leq 1.00$
Bottomskin	Moment	$uc_{\text{bs},\sigma} = 0.18$	$\leq 1.00$
Webs	Shear	$uc_{\text{w},\tau} = 0.93$	$\leq 1.00$
	Compression	$uc_{\text{w},\sigma} = 0.33$	$\leq 1.00$
Bolts of the railing		$uc_{\text{b},l} = (0.19 \quad 0.02 \quad 0.15)$	$\leq 1.00$
Flange	Compression around holes	$uc_{\text{f},\text{b},\sigma_{\text{yc}}} = 0.01$	$\leq 1.00$
	Tension around holes	$uc_{\text{f},\text{b},\sigma_{\text{yt}}} = 0.01$	$\leq 1.00$
	Shear around holes	$uc_{\text{f},\text{b},\tau_{\text{yz}}} = (0.00 \quad 0.18)$	$\leq 1.00$
Threaded Rods		$uc_{\text{d}} = (0.02 \quad 0.01)$	$\leq 1.00$
Support flange	Compression around holes	$uc_{\text{sf},\sigma_{\text{c}}} = (0.08 \quad 0.04)$	$\leq 1.00$
	Tension around holes	$uc_{\text{sf},\sigma_{\text{t}}} = (0.05 \quad 0.02)$	$\leq 1.00$
	Shear around holes	$uc_{\text{sf},\tau} = 0.02$	$\leq 1.00$

The bridge is checked on bouyance and is heavy enough to counter the uplift force due to bouyancy.

### Total thermal expansion/contraction of the bridge


Length direction	Expansion	$\Delta L_{\text{dek.exp}} = 4.4 \cdot \text{mm}$
	Contraction	$\Delta L_{\text{dek.con}} = 2.6 \cdot \text{mm}$
Width direction	Expansion	$\Delta B_{\text{dek.exp}} = 1.8 \cdot \text{mm}$
	Contraction	$\Delta B_{\text{dek.con}} = 1.1 \cdot \text{mm}$

### Total thermal expansion/contraction for the dilatations

Length direction	Expansion	$\Delta L_{\text{dil.exp}} = 5.8 \cdot \text{mm}$
	Contraction	$\Delta L_{\text{dil.con}} = 4.0 \cdot \text{mm}$
Width direction	Expansion	$\Delta B_{\text{dil.exp}} = 2.4 \cdot \text{mm}$
	Contraction	$\Delta B_{\text{dil.con}} = 1.7 \cdot \text{mm}$

# Engineering Case Study

## Ordnance Bridge United Kingdom



## Table of content

	Page
1. Introduction	3
2. Design principle and geometry of the deck	4
3. Construction principle: InfraCore Inside	5
4. Laminate- & mechanical properties of the cross-section	6
5. Actions, combinations of actions & partial factors	7
5.1 Actions	7
5.2 Combinations of actions	7
5.3 Partial factors	8
6 Thermal behaviour	9
7. Check on serviceability, SLS	10
7.1 Eigenfrequency & Accelerations	10
7.2 Deformations	10
7.3 Camber & Gradient	10
8. Check on safety, ULS	11
8.1 Strength of the skins	11
8.2 Strength of the webs	11
8.3 Strength of the fixation of the railing	12
8.4 Strength of the flanges	13
8.5 Strength of the fixation of the bridge	14
8.6 Strength of the support flanges	15
9. Actions on abutments	17
10. Conclusion	18
Corresponding drawings	
- 17-294-OR-010-TKK-1-Deck_R1.0	

Rev	Status	Date	Author	Track changes
1.0	Final	10-1-2018	FZ	Initial version

## 1. Introduction

This report describes the construction of the new InfraCore Inside pedestrian bridge The Ordnance bridge near the river Lee in England, designed and built by FiberCore Europe (Rotterdam, The Netherlands) commissioned by ECS Engineering Services.

This bridge has a length of  $L_{rd} = 9.00\text{m}$  and a width of  $B_{tot} = 1.50\text{m}$ .

The InfraCore Inside bridge is an integral structure made from fiber-reinforced polymers (FRP), more specifically glassfibers in combination with a polyester matrix (glassfiber reinforced polyester or GFRP). The glassfibers carry the loads acting on the bridge, the matrix supports the fibers, transfers loads between fibers and gives the bridge its shape.

GFRP has a high specific strength (strength vs specific weight), resulting in relatively lightweight structures (bridges) capable of carrying large loads with high margins of safety.

The bridge has been designed according to Eurocodes, including British national annexes, and CUR-recommendation 96.

FiberCore Europe is responsible for the engineering and manufacturing of the composite bridge.



## 2. Design principles and geometry of the decks

The InfraCore Inside decks are designed in compliance with the following relevant standards:


- EN 1990+A1+A1/C2:2011, "Eurocode 0: Basis of structural design"
  - EN 1991-2+C1:2011, "Eurocode 1: Actions on structures - Part 2: Traffic loads on bridges"
  - EN 1991-1-5+C1:2011, "Eurocode 1: Actions on structures - Part 5: General actions - Thermal actions"
  - [EUR23984] "Design of Lightweight Foot-Bridges for Human Induced Vibrations"
  - [CUR-recommendation 96:2003] "Fibre reinforced plastics in civil engineering supporting frameworks"
- 
- Technical design life            100yr
  - Consequence class                CC1
  - Traffic class                        TC3

The main parameters describing the design of the considered deck are given below. For more details on the geometry of the decks, refer to the accompanying drawing.

Total length	$L_{\text{tot}} = 9 \cdot \text{m}$
Length of deck	$L_{\text{rd}} = 9 \cdot \text{m}$
Span	$L_{\text{O}} = 8.6 \cdot \text{m}$
Width	$B_{\text{tot}} = 1.5 \text{ m}$
Effective width (between railings)	$B_{\text{eff}} = 1.2 \text{ m}$
Construction height	$H_{\text{b}} = 170 \cdot \text{mm}$
Width flange	$B_{\text{fh}} = 200 \cdot \text{mm}$
Total surface area	$A_{\text{bridge}} = 13.5 \text{ m}^2$
Total mass	$M_{\text{tot}} = 1.9 \times 10^3 \cdot \text{kg}$
Assumed mass of the railing per meter	$M_{\text{L.rail}} = 50 \text{ kg} \cdot \text{m}^{-1}$

The bridge is assumed to be simply supported on the two abutments beneath the two bulkheads. Both abutments are acting as line supports for the bridge where all webs are supported such that the loads are transferred from the webs through the bulkheads into the abutments.

The bridge will be fixed in longitudinal and transverse direction at one abutment. The bridge will be fixed in transverse direction and will be free to move in longitudinal direction and at the second abutment to accommodate the thermal expansion. The fixation is done with threaded rods through the bottom of the bridge.




### 3. Construction principle: InfraCore Inside

The bridge is produced as an InfraCore Inside structure (ICI). An ICI structure can be described as a sandwich structure with two FRP skins at the top and bottom of the bridge, and an FRP-reinforced foam core. The core reinforcement consists of FRP shear webs in longitudinal (flat) direction of the bridge.

Skins and longitudinal shear webs are constructed from the same base materials, in this case non-crimp fabrics, running through the topskin, a shear web and the bottomskin. This ensures a durable, fiber-reinforced connection between skins and shear webs, eliminating the risk of skin-core debonding. Such a layer connecting both skins through the core are called Z-layers, after the shape of each of these layers. To add stiffness or strength, extra material can be added to the skin and/or shear webs.

The stacking sequence of fabrics results in a layered structure (a laminate), each layer called a ply.

All fibers are E-glass fibers, the matrix is a polyester resin.



## 4 Laminate- & mechanical properties of the cross-section

The applied laminates are anisotropic. The local coordinate systems of each laminate is orientated as follows:

x axis: in-plane, in span direction of the bridge  
y axis: in-plane, perpendicular to the span direction of the bridge  
z axis: out of plane, perpendicular to the laminate

Multiple different laminates, with each their own properties, are applied in the bridge. The laminate properties are calculated with standard micromechanics models and classical lamination theory as is stated in the CUR96.

The used properties used in the calculations are listed here:

Topskin	$t_{ts} = 12 \cdot \text{mm}$	$E_{x,ts} = 32 \cdot \text{GPa}$	$E_{y,ts} = 19 \cdot \text{GPa}$	
	$\sigma_{x,ts} = 386 \cdot \text{MPa}$	$\sigma_{y,ts} = 226 \cdot \text{MPa}$	$\tau_{xy,ts} = 98 \cdot \text{MPa}$	
Bottomskin	$t_{bs} = 12 \cdot \text{mm}$	$E_{x,bs} = 34 \cdot \text{GPa}$	$E_{y,bs} = 17 \cdot \text{GPa}$	
	$\sigma_{x,bs} = 413 \cdot \text{MPa}$	$\sigma_{y,bs} = 199 \cdot \text{MPa}$	$\tau_{xy,bs} = 98 \cdot \text{MPa}$	
Flange	$t_f = 20 \cdot \text{mm}$	$E_{x,f} = 26 \cdot \text{GPa}$	$E_{y,f} = 26 \cdot \text{GPa}$	$G_{xy,f} = 6 \cdot \text{GPa}$
	$\sigma_{x,f} = 306 \cdot \text{MPa}$	$\sigma_{y,f} = 306 \cdot \text{MPa}$	$\tau_{xy,f} = 98 \cdot \text{MPa}$	$\tau_{yz,f} = 39 \cdot \text{MPa}$
Edge	$t_e = 13 \cdot \text{mm}$	$E_{x,e} = 26 \cdot \text{GPa}$	$E_{y,e} = 26 \cdot \text{GPa}$	$G_{xy,e} = 6 \cdot \text{GPa}$
	$\sigma_{x,e} = 306 \cdot \text{MPa}$	$\sigma_{y,e} = 306 \cdot \text{MPa}$	$\tau_{xy,e} = 98 \cdot \text{MPa}$	
Webs	$t_w = 5 \cdot \text{mm}$	$E_{x,w} = 12 \cdot \text{GPa}$	$E_{y,w} = 12 \cdot \text{GPa}$	$G_{xy,w} = 4 \cdot \text{GPa}$
	$\sigma_{x,w} = 143 \cdot \text{MPa}$	$\sigma_{y,w} = 143 \cdot \text{MPa}$	$\tau_{xy,w} = 64 \cdot \text{MPa}$	
Support flange	$t_{sf} = 10 \cdot \text{mm}$	$E_{x,sf} = 26 \cdot \text{GPa}$	$E_{y,sf} = 26 \cdot \text{GPa}$	$G_{xy,sf} = 6 \cdot \text{GPa}$
	$\sigma_{x,sf} = 306 \cdot \text{MPa}$	$\sigma_{y,sf} = 306 \cdot \text{MPa}$	$\tau_{xy,sf} = 98 \cdot \text{MPa}$	


The normal, bending and shear stiffness of the bridge are calculated by the summation of the property of each independent laminate. Only the webs and edges taken into account in the calculation of the shear stiffness.

$$EA_x = 1.2 \times 10^9 \cdot \text{N} \quad EI_{yy} = 7 \cdot \text{MN} \cdot \text{m}^2 \quad GA_{xz} = 3.8 \times 10^7 \cdot \text{N}$$

The thermal behaviour of the bridge is dominated by the skins. The thermal expansion coefficient of the top and bottomskins can vary a bit from each other due to a small difference in lay-up. The average thermal expansion coefficient of both skins is taken to determine the thermal behaviour of the bridge.

$$\alpha_x = 11.6 \times 10^{-6} \cdot \text{K}^{-1} \quad \alpha_y = 19.5 \times 10^{-6} \cdot \text{K}^{-1}$$

Cross-section of the construction



## 5 Actions, combination of actions & partial factors

### 5.1 Actions

#### Permanent loads

The permanent load on the bridge is its self-weight of the structural and non-structural members. The structural member is the InfraCore Inside GFRP bridge deck. The non structural members are the wear surface and railings.

$$\text{Total self-weight as distributed load} \quad q_m = M_{\text{tot}} \cdot g \cdot A_{\text{bridge}}^{-1} = 1.3 \cdot \text{kN} \cdot \text{m}^{-2}$$

#### Live loads

The normative live loads that are taken into account are given below. Live loads, like wind and snow loads, not mentioned are assumed to be not normative and therefore not taken into account in the design. This assumption is based on the combination rules and combination factors listed in EN1990.

$$\text{Uniform distributed load [EC-1]} \quad q_{fk} = 5 \cdot \text{kN} \cdot \text{m}^{-2}$$

$$\begin{aligned} \text{Concentrated load [EC-1]} \\ \text{Load} \quad Q_{fwb} &= 10 \cdot \text{kN} \\ \text{Acting on square surface with sides} \quad B_{fwb} &= 0.1 \cdot \text{m} \end{aligned}$$

$$\begin{aligned} \text{Horizontal load [EC-1]} \\ \text{Due to uniform distributed load} \quad Q_{fk,q} &= 5 \cdot \text{kN} \end{aligned}$$

$$\begin{aligned} \text{Dense crowd for dynamic response [EUR23984]} \\ \text{Mass of one person} \quad P_1 &= 800 \text{ N} \\ \text{Density crowd} \quad d_{TC} &= 0.5 \cdot P_1 \cdot \text{m}^{-2} \end{aligned}$$

$$\begin{aligned} \text{Load on railings [EC-1]} \\ \text{Line load on top of railing} \quad q_{lk} &= 1.0 \cdot \text{kN} \cdot \text{m}^{-1} \end{aligned}$$

#### Accidental loads

There are no accidental loads taken into account for this bridge.

### 5.2 Combination of actions

The combinations of actions on this bridge are based on formula 6.10b EN1990 6.4.3.2 and the tables in EN1990, A2.2.6 and are listed below. The design of the bridge is dominated by its serviceability (stiffness) when loaded with the live loads. All load combinations are used to check the safety (strength) of the bridge.

LC =	"-"	"LC0"	"LC1"	"LC3"
	"Load"	"EG"	"gr1"	"Qfwb"
	"q.EG"	1	1	1
	"q.fk"	0	1	0
	"Q.fk,q"	0	1	0
	"Q.fwb"	0	0	1



### 5.3 Partial factors

The used partial factors are given in the Eurocode and CUR-recommendation 96. The consequence class of this bridge is defined as CC1 ( $K_{FI} = 0.9$ ). The CUR defines different conversion factors to take into account the effect on the material properties of different sources. Which conversion factors are taken into account are depending on the situation and type of load.

Material factors	Scatter in material properties		$\gamma_{m1} = 1.35$
	Production proces		$\gamma_{m2} = 1.20$
Conversion factors	Temperature (t)		$\gamma_{ct} = 1.10$
	Moisture (v)		$\gamma_{cv} = 1.10$
	Fatigue (f)		$\gamma_{cf} = 1.10$
	Creep (k)		$\gamma_{ck} = 1.24$
Factors for the service limit state (SLS)			
Load factor			$\gamma_f = 1.00$
Material factor			$\gamma_{m.SLS} = 1.00$
Conversion factors	Vibrations	Permanent loads (t,v,f)	$\gamma_{cv.p} = 1.33$
		Live loads (t,v)	$\gamma_{cv.l} = 1.21$
	Deformations	Permanent loads (t,v,f,k)	$\gamma_{cd.p} = 1.65$
		Live loads (t,v,f)	$\gamma_{cd.l} = 1.21$
Factors for the ultimate limit state (ULS)			
Load factors	Permanent loads		$\gamma_G = 0.89 \cdot 1.35 \cdot K_{FI} = 1.08$
	If favorable		$\gamma_{G.inf} = 0.89 \cdot 1.0 = 0.89$
	Live loads		$\gamma_Q = 1.35 \cdot K_{FI} = 1.22$
Material factors(m1, m2)			$\gamma_{m.ULS} = 1.62$
Conversion factors	Strength	Permanent loads (t,v,k)	$\gamma_{cs.p} = 1.50$
		Live loads (t,v)	$\gamma_{cs.l} = 1.21$
Additional reductionfactor due to the productionproces (ULS)			
Topskin			$\gamma_{ts} = 1.18$
Bottomskin			$\gamma_{bs} = 1.12$
Webs			$\gamma_w = 1.47$

Some fibers/layers are locally interrupted in the construction due to the production proces. These interruptions, which are very locally, are resulting in local weaker spots in the construction. The additional reduction factors are taken into account for the ULS (strength) to compensate the interruption of the fibers. These interruptions have no significant influence on the stiffness of the bridge. Therefore they are not taken into account in the SLS.

## 6 Thermal behaviour of the bridge

Due to changes in temperature the bridge deck will contract/expand in longitudinal en transverse direction. The temperature components are derived from the EN 1991-1-5+C1:2011. This design is more of type 1 than any of the other types.

Design temperature	$T_0 = 10 \cdot ^\circ\text{C}$
Minimal temperature in the shadow	$T_{\min} = -18 \cdot ^\circ\text{C}$
Maximum temperature in the shadow	$T_{\max} = 34 \cdot ^\circ\text{C}$
Temperature difference between shadow - bridge	$\Delta T_{e,\min} = -3 \cdot ^\circ\text{C}$ $\Delta T_{e,\max} = 16 \cdot ^\circ\text{C}$
Temperature difference component	$\Delta T_{M\text{heat}} = 30 \cdot ^\circ\text{C}$ $\Delta T_{M\text{cool}} = 8 \cdot ^\circ\text{C}$
Additional temperature difference for expansion joints	$\Delta T_{\text{dil}} = 20 \cdot ^\circ\text{C}$
Combination factors	$\omega_N = 0.35$ $\omega_M = 0.75$
Uniform temperature component bridge	$T_{e,\min} = T_{\min} + \Delta T_{e,\min} = -21 \cdot ^\circ\text{C}$ $T_{e,\max} = T_{\max} + \Delta T_{e,\max} = 50 \cdot ^\circ\text{C}$ $\Delta T_N = T_{e,\max} - T_{e,\min} = 71 \cdot ^\circ\text{C}$
Maximum temperature change contraction	$\Delta T_{N,\text{con}} = T_0 - T_{e,\min} = 31 \cdot ^\circ\text{C}$
Maximum temperature change expansion	$\Delta T_{N,\text{exp}} = T_{e,\max} - T_0 = 40 \cdot ^\circ\text{C}$

Normative temperature combination for the bridge and expansion joints

$$\begin{aligned}\Delta T_{\text{exp}} &= \max(\Delta T_{M\text{heat}} + \omega_N \cdot \Delta T_{N,\text{exp}}, \omega_M \cdot \Delta T_{M\text{heat}} + \Delta T_{N,\text{exp}}) = 63 \cdot ^\circ\text{C} \\ \Delta T_{\text{con}} &= \max(\Delta T_{M\text{cool}} + \omega_N \cdot \Delta T_{N,\text{con}}, \omega_M \cdot \Delta T_{M\text{cool}} + \Delta T_{N,\text{con}}) = 37 \cdot ^\circ\text{C} \\ \Delta T_{d,e} &= \max[\Delta T_{M\text{heat}} + \omega_N \cdot (\Delta T_{N,\text{exp}} + \Delta T_{\text{dil}}), \omega_M \cdot \Delta T_{M\text{heat}} + (\Delta T_{N,\text{exp}} + \Delta T_{\text{dil}})] = 83 \cdot ^\circ\text{C} \\ \Delta T_{d,c} &= \max[\Delta T_{M\text{cool}} + \omega_N \cdot (\Delta T_{N,\text{con}} + \Delta T_{\text{dil}}), \omega_M \cdot \Delta T_{M\text{cool}} + (\Delta T_{N,\text{con}} + \Delta T_{\text{dil}})] = 57 \cdot ^\circ\text{C}\end{aligned}$$

Maximum expansion/contraction due to the normative temperature components

Bridge	Total expansion joints
$\Delta L_{\text{dek.exp}} = \Delta T_{\text{exp}} \cdot \alpha_x \cdot L_{\text{rd}} = 6.5 \cdot \text{mm}$	$\Delta L_{\text{dil.exp}} = \Delta T_{d,e} \cdot \alpha_x \cdot L_{\text{rd}} = 8.6 \cdot \text{mm}$
$\Delta L_{\text{dek.con}} = \Delta T_{\text{con}} \cdot \alpha_x \cdot L_{\text{rd}} = 3.9 \cdot \text{mm}$	$\Delta L_{\text{dil.con}} = \Delta T_{d,c} \cdot \alpha_x \cdot L_{\text{rd}} = 5.9 \cdot \text{mm}$
$\Delta B_{\text{dek.exp}} = \Delta T_{\text{exp}} \cdot \alpha_y \cdot B_{\text{tot}} = 1.8 \cdot \text{mm}$	$\Delta B_{\text{dil.exp}} = \Delta T_{d,e} \cdot \alpha_y \cdot B_{\text{tot}} = 2.4 \cdot \text{mm}$
$\Delta B_{\text{dek.con}} = \Delta T_{\text{con}} \cdot \alpha_y \cdot B_{\text{tot}} = 1.1 \cdot \text{mm}$	$\Delta B_{\text{dil.con}} = \Delta T_{d,c} \cdot \alpha_y \cdot B_{\text{tot}} = 1.7 \cdot \text{mm}$

The fixation of the bridge with one foundation has slotted holes such that the bridge can freely expand/contract. Therefore, there will be no significance thermal stresses in the construction.

## 7 Check on serviceability, SLS

The following design requirements are applicable to the design in order to ensure that the use of the bridge is comfortable.

- Minimum eigenfrequency of 3.5 Hz when unloaded
- Minimum eigenfrequency of 2.3 Hz when loaded with the dense crowd
- Maximum deflection of  $\delta_{all} = \frac{L_0}{100} = 86 \cdot \text{mm}$  under live loads
- Maximum gradient of  $\varphi_{max} = 4.0\%$  to ensure easy and good accessibility
- Average gradient of minimal  $\varphi_{avg} = 0.5\%$  to ensure good drainage of the bridge

### 7.1 Eigenfrequency

The bridge is modelled as a simply supported beam. The first eigenfrequency of a simply supported beam is calculated with:

$$f(K, d_{TC}) = \frac{K}{2\pi} \cdot \sqrt{\frac{EI_{yy} \cdot g \cdot \gamma_{m.SLS}^{-1}}{(\gamma_{cv.p} \cdot q_m \cdot B_{tot} + \gamma_{cv.l} \cdot d_{TC} \cdot B_{eff}) \cdot L_0^4}}$$

Where constant  $K_{ss,0} = 9.87$  and dependent on the boundary conditions and which eigenfrequency is evaluated. In previous research it is concluded that the calculated eigenfrequency can increased with 18% due to the fact that the support conditions in reality are not fully simply supported. This 18% is determined with a confidence level of 95%.

First eigenfrequency, unloaded bridge  $f_{0.unloaded} = f(1.18 \cdot K_{ss,0}, 0) = 3.9 \cdot \text{Hz}$

First eigenfrequency, loaded bridge  $f_{0.loaded} = f(1.18 \cdot K_{ss,0}, d_{TC}) = 3.6 \cdot \text{Hz}$

The eigenfrequencies are high enough to avoid uncomfortable accelerations.

### 7.2 Deformations

The deformations due to the live loads are calculated with the beam theory.

Deformation load combination 1, uniform distributed load

$$\delta_{LC1} = \frac{5}{384} \cdot \frac{q_{fk} \cdot B_{eff} \cdot L_0^4}{EI_{yy}} + \frac{1}{8} \cdot \frac{q_{fk} \cdot B_{eff} \cdot L_0^2}{GA_{xz}} = 65 \cdot \text{mm}$$

$$\delta_{LC1.k} = \gamma_f \cdot \gamma_{m.SLS} \cdot \gamma_{cd.l} \cdot \delta_{LC1} = 79 \cdot \text{mm}$$

Unity checks  $uc_{\delta.LC1} = \frac{\delta_{LC1.k}}{\delta_{all}} = 0.92$

### 7.3 Camber & Gradient

The bridge is produced with a constant radius. The camber maximum and average gradient during production, begin design life (self weight taken into account) and end design life (creep and material degradation taken into account) are:

Bulge <sub>p</sub> = 84 · mm	Bulge <sub>i</sub> = 62 · mm	Bulge <sub>e</sub> = 48 · mm
$\varphi_{max.p} = 3.8 \cdot \%$	$\varphi_{max.i} = 2.8 \cdot \%$	$\varphi_{max.e} = 2.1 \cdot \%$
$\varphi_{avg.p} = 1.9 \cdot \%$	$\varphi_{avg.i} = 1.4 \cdot \%$	$\varphi_{avg.e} = 1.1 \cdot \%$

The maximum and average gradient are satisfying the requirements for the accessibility and drainage of the bridge.

## 8 Check on safety (ULS)

The laminates of the skins, webs and flanges are checked on their strengths for the most critical load combinations. the fixation of the railings and of the bridge to the foundations are also checked on their strength.

### 8.1 Strength of the skins

The strength of the skins is checked for load combination 1.

Maximum bending moments

Self weight  $M_m = \frac{1}{8} \cdot q_m \cdot B_{tot} \cdot L_o^2 = 19 \cdot \text{kN} \cdot \text{m}$

Uniform distributed load  $M_q = \frac{1}{8} \cdot q_{fk} \cdot B_{tot} \cdot L_o^2 = 69 \cdot \text{kN} \cdot \text{m}$

Per load combination  $M_{LC1} = \gamma_m \cdot UGT \cdot (\gamma_G \cdot \gamma_{cs,p} \cdot M_m + \gamma_Q \cdot \gamma_{cs,l} \cdot M_q) = 214 \cdot \text{kN} \cdot \text{m}$

Stress in the skins

Distance of topskin to neutralline  $z_{ts} = 73 \cdot \text{mm}$

Distance of bottomskin to neutralline  $z_{bs} = -97 \cdot \text{mm}$

Second moment of inertia of the skins  $I_h = 1.7 \times 10^8 \cdot \text{mm}^4$

Stress in topskin  $\sigma_{ts,x,M} = \frac{\gamma_{ts} \cdot M_{LC1} \cdot z_{ts}}{I_h} = 111 \cdot \text{MPa}$

Stress in bottomskin  $\sigma_{bs,x,M} = \frac{\gamma_{bs} \cdot M_{LC1} \cdot z_{bs}}{I_h} = -140 \cdot \text{MPa}$

Allowable stress in the skins

Topskin  $\sigma_{x,ts} = 386 \cdot \text{MPa}$

Bottomskin  $\sigma_{x,bs} = 413 \cdot \text{MPa}$

Unity checks  $uc_{ts,\sigma} = \frac{|\sigma_{ts,x,M}|}{\sigma_{x,ts}} = 0.29$   $uc_{bs,\sigma} = \frac{|\sigma_{bs,x,M}|}{\sigma_{x,bs}} = 0.34$

### 8.2 Strength of the webs

The strength of the webs is checked on shear for load combination 1 and 3 and on compression for load combination 3.

All the webs are considered to be the thin web of a I-beam with thick flanges. The shear stress is calculated with  $\tau = \frac{V}{A}$  where A is the cross-sectional area of the web. The height of the webs are taken as the distance between the two centroids of the top and bottomskins. the center-to-center distance of the webs is  $c_{cw} = 210 \cdot \text{mm}$

Maximum shear force one web

Self weight  $V_m = \frac{1}{2} q_m \cdot c_{cw} \cdot L_o = 1.2 \cdot \text{kN}$

Uniform distributed load  $V_q = \frac{1}{2} q_{fk} \cdot c_{cw} \cdot L_o = 4.5 \cdot \text{kN}$

Concentrated load  $V_{fwk} = Q_{fwk} = 10.0 \cdot \text{kN}$

Per load combination

$V_{LC1} = \gamma_w \cdot \gamma_m \cdot UGT \cdot (\gamma_G \cdot \gamma_{cs,p} \cdot V_m + \gamma_Q \cdot \gamma_{cs,l} \cdot V_q) = 21 \cdot \text{kN}$

$V_{LC3} = \gamma_w \cdot \gamma_m \cdot UGT \cdot (\gamma_G \cdot \gamma_{cs,p} \cdot V_m + \gamma_Q \cdot \gamma_{cs,l} \cdot V_{fwk}) = 40 \cdot \text{kN}$



Shearstress in web

Cross-section area of one web

$$A_w = t_w \cdot \left( H_b - \frac{t_{ts} + t_{bs}}{2} \right) = 796 \cdot \text{mm}^2$$

Shear stress

$$\tau_{w.xy,V} = \max(V_{LC1}, V_{LC3}) \cdot A_w^{-1} = 50 \cdot \text{MPa}$$

Allowable shear stress

$$\tau_{xy,w} = 64 \cdot \text{MPa}$$

Unity check

$$uc_{w,\tau} = \frac{\tau_{w.xy,V}}{\tau_{xy,w}} = 0.78$$

The maximum compression stress in one web occurs when the concentrated load is placed directly above the web and is calculated with  $\sigma = \frac{P}{A}$ .

The maximum compression force on one web (load and material factors included):

$$P_{LC3} = \gamma_{m,ULS} \cdot (\gamma_{cs,p} \cdot \gamma_G \cdot q_m \cdot c_w \cdot B_{fwk} + \gamma_{cs,l} \cdot \gamma_Q \cdot Q_{fwk}) = 24 \cdot \text{kN}$$

The maximum compression stress in one web:  $\sigma_{w,max} = \frac{P_{LC3}}{B_{fwk} \cdot t_w} = 47 \cdot \text{MPa}$

Design strength of the web

$$\sigma_{y,w} = 143 \cdot \text{MPa}$$

Unity check

$$uc_{w,\sigma} = \frac{\sigma_{w,max}}{\sigma_{y,w}} = 0.33$$

### 8.3 Strength of the fixation of the railing

It is assumed that the railings are fixed to the flange with 2 pairs of bolts. The strength of the bolts is checked on the situation that the railing is loaded with the line load on the top rail.

Height of the railing

$$H_{rail} = 1.2 \text{ m}$$

Spacing stanchion

$$s_{stan} = 1.5 \text{ m}$$

Diameter bolt, metric

$$d_{b,l} = 12 \cdot \text{mm}$$

class of the bolt

$$klasse_{b,l} = 8.8$$

c-c distance bolts

x direction

$$c_{x,b} = 120 \cdot \text{mm}$$

y direction

$$c_{y,b} = 80 \cdot \text{mm}$$

Edge distance bolt - baseplate

x direction

$$e_{x,base} = 30 \cdot \text{mm}$$

y direction

$$e_{y,base} = 30 \cdot \text{mm}$$

Edge distance bolt - edge laminate

$$e_{y,b} = 50 \cdot \text{mm}$$

Load on one bolt

Tensile

$$F_{t,b} = \frac{\gamma_{Q1} \cdot q_{lk} \cdot s_{stan} \cdot H_{rail}}{2 \cdot \left( \frac{e_{y,base}^2}{e_{y,base} + c_{y,b}} + e_{y,base} + c_{y,b} \right)} = 9 \cdot \text{kN}$$

Shear

$$F_{v,b} = \frac{1}{4} (\gamma_{Q1} \cdot q_{lk} \cdot s_{stan}) = 0.5 \cdot \text{kN}$$

Allowable load on one bolt

Tensile  $F_{t.b.alw} = 49 \cdot \text{kN}$

Shear  $F_{v.b.alw} = 27 \cdot \text{kN}$

Unity check 
$$uc_{b,l} = \left( \frac{F_{t,b}}{F_{t.b.alw}} + \frac{F_{v,b}}{F_{v.b.alw}} + \frac{F_{v,b}}{F_{v.b.alw}} + \frac{F_{t,b}}{1.4F_{t.b.alw}} \right) = (0.19 \quad 0.02 \quad 0.15)$$

## 8.4 Strength of the flanges

The strength of the flanges is checked around the connections of the standions

Diameter hole  $d_{g,l} = 14 \cdot \text{mm}$

Diameter washer  $d_{r,l} = 40 \cdot \text{mm}$

### Laminate around the holes for the bolts

Allowable stress in y direction 
$$\sigma_{y.f.alw} = \frac{\sigma_{y.f}}{\gamma_{m.ULS} \cdot \gamma_{cs,l}} = 156 \cdot \text{MPa}$$

Allowable shear stress in xy plane 
$$\tau_{xy.f.alw} = \frac{\tau_{xy.f}}{\gamma_{m.ULS} \cdot \gamma_{cs,l}} = 50 \cdot \text{MPa}$$

Allowable shear stress in yz plane 
$$\tau_{yz.f.alw} = \frac{\tau_{yz.f}}{\gamma_{m.ULS} \cdot \gamma_{cs,l}} = 20 \cdot \text{MPa}$$

Compressive stresses

Stress concentration factor 
$$K_c = \left( \frac{d_{g,l}}{d_{b,l}} \right)^2 = 1.36$$

Compressive stress 
$$\sigma_{f.b.y,c} = \frac{F_{v,b} \cdot K_c}{d_{g,l} \cdot t_f} = 2.2 \cdot \text{MPa}$$

Unity check

$$uc_{f.b.\sigma yc} = \frac{\sigma_{f.b.y,c}}{\sigma_{y.f.alw}} = 0.01$$

Tensile stresses

The tensile stresses around the holes are calculated according to the theory published in "Peterson's stress concentration factors" author Walter D. Pilkey and Deborah F. Pilkey, 2008. The graph used to determine the stress concentration factor is republished in the figure below

Ratio diameter hole - c\_c distance holes 
$$r_{g,b,l} = \frac{d_{g,l}}{c_{x,b}} = 0.12$$

Stress concentration factor  $K_t = 8$

Tensile stress 
$$\sigma_{f.b.y,t} = \frac{K_t \cdot F_{v,b}}{(c_{x,b} - d_{g,l}) \cdot t_f} = 1.7 \cdot \text{MPa}$$

Unity check


$$uc_{f.b.\sigma yt} = \frac{\sigma_{f.b.y,t}}{\sigma_{y.f.alw}} = 0.01$$

Shear stress

$$\text{Shear stress due to shear out} \quad \tau_{f.b.xy.s} = \frac{F_{v.b}}{2 \cdot e_{y.b} \cdot t_f} = 0.2 \cdot \text{MPa}$$

$$\text{Shear stress due to pull-through} \quad \tau_{f.b.yz.p} = \frac{F_{t.b}}{\pi \cdot d_{r.l} \cdot t_f} = 3.6 \cdot \text{MPa}$$

$$\text{Unity check} \quad uc_{f.b.\tau yz} = \left( \frac{\tau_{f.b.xy.s}}{\tau_{xy.f.alw}} \quad \frac{\tau_{f.b.yz.p}}{\tau_{yz.f.alw}} \right) = (0.00 \quad 0.18)$$



## 8.5 Strength of the fixation of the bridge

The bridge is fixed to the two abutments with threaded rods. These rods are fitted through the holes in the support flanges which are attached to the bottomside of the bridge. In one of the flanges, the holes are slotted such that the thermal expansion or contraction of the bridge doesn't lead to thermal stresses. One function of these rods is to transfer the horizontal force to the abutments.

The threaded rods

Total number of rods	$n_d = 4$
Number of load bearing rods in x direction	$n_{d,x} = 2$
Number of load bearing rods in y direction	$n_{d,y} = 4$
Diameter rods, metric	$d_d = 24 \cdot \text{mm}$
Diameter washer	$d_{d,r} = 72 \text{mm}$
Material class	$\text{klasse}_d = 8.8$
Diameter hole	$d_{g,d} = 32 \cdot \text{mm}$
Edge laminate - hole distance	$e_{x,d} = 100 \cdot \text{mm}$

Load per rod

$$\text{Shear in x direction} \quad F_{v.x.LC1} = \frac{\gamma_Q \cdot Q_{flk.q}}{n_{d,x}} = 3 \cdot \text{kN}$$

$$\text{Shear in y direction} \quad F_{v.y.LC1} = \frac{\gamma_Q \cdot Q_{flk.q}}{n_{d,y}} = 2 \cdot \text{kN}$$

Allowable shear force on one rod

$$F_{v.d.alw} = 112 \cdot \text{kN}$$

$$\text{Unity check} \quad uc_d = \left( \frac{F_{v.x.LC1}}{F_{v.d.alw}} \quad \frac{F_{v.y.LC1}}{F_{v.d.alw}} \right) = (0.03 \quad 0.01)$$

## 8.6 Strength of the support flanges

The laminate around the holes for the rods is checked on strength.

$$\text{Allowable stress in x direction} \quad \sigma_{x.sf.alw} = \frac{\sigma_{x.sf}}{\gamma_{m.ULS} \cdot \gamma_{cs.l}} = 156 \cdot \text{MPa}$$

$$\text{Allowable stress in y direction} \quad \sigma_{y.sf.alw} = \frac{\sigma_{y.sf}}{\gamma_{m.ULS} \cdot \gamma_{cs.l}} = 156 \cdot \text{MPa}$$

$$\text{Allowable shear stress in xy direction} \quad \tau_{xy.sf.alw} = \frac{\tau_{xy.sf}}{\gamma_{m.ULS} \cdot \gamma_{cs.l}} = 50 \cdot \text{MPa}$$

Compressive stress

$$\text{Stress concentration factor} \quad K_c = \left( \frac{d_{g,d}}{d_d} \right)^2 = 1.78$$

$$\text{Compressive stress in x direction} \quad \sigma_{sf.x.c} = \frac{F_{v.x.LC1} \cdot K_c}{d_{g,d} \cdot t_{sf}} = 18 \cdot \text{MPa}$$

$$\text{Compressive stress in y direction} \quad \sigma_{sf.y.c} = \frac{F_{v.y.LC1} \cdot K_c}{d_{g,d} \cdot t_{sf}} = 9 \cdot \text{MPa}$$

$$\text{Unity check} \quad u_{c_{sf,\sigma c}} = \left( \frac{\sigma_{sf.x.c}}{\sigma_{x.sf.alw}} \quad \frac{\sigma_{sf.y.c}}{\sigma_{y.sf.alw}} \right) = (0.12 \quad 0.06)$$

Tensile stress

The loaded width is limited due to the limited edge laminate - hole distance.

$$\text{Loaded width} \quad B_{eff,d} = d_{g,d} + 2 \cdot e_{x,d} = 232 \cdot \text{mm}$$

$$\text{Ratio hole diameter - loaded width} \quad r_{g,b,d} = \frac{d_{g,d}}{B_{eff,d}} = 0.14$$

$$\text{Stress concentration factor} \quad K_t = 6.5$$

$$\text{Tensile stress in x direction} \quad \sigma_{sf.x.t} = \frac{K_t \cdot F_{v.x.LC1}}{(B_{eff,d} - d_{g,d}) \cdot t_{sf}} = 11 \cdot \text{MPa}$$

$$\text{Tensile stress in y direction} \quad \sigma_{sf.y.t} = \frac{K_t \cdot F_{v.y.LC1}}{(B_{eff,d} - d_{g,d}) \cdot t_{sf}} = 5 \cdot \text{MPa}$$

$$\text{Unity check} \quad u_{c_{sf,\sigma t}} = \left( \frac{\sigma_{sf.x.t}}{\sigma_{x.sf.alw}} \quad \frac{\sigma_{sf.y.t}}{\sigma_{y.sf.alw}} \right) = (0.07 \quad 0.03)$$

Shear stress

$$\text{Shear stress due to shear out} \quad \tau_{sf.xy.s} = \frac{\max(F_{v.x.LC1}, F_{v.y.LC1})}{2 \cdot e_{x,d} \cdot t_{sf}} = 2 \cdot \text{MPa}$$

$$\text{Unity check} \quad u_{c_{sf,\tau}} = \frac{\tau_{sf.xy.s}}{\tau_{xy.sf.alw}} = 0.03$$



### Check on buoyancy

The buoyancy will be determined by calculating the buoyancy force using Archimede's principle.

The volume of water displaced by the bridge  $V_{\text{tot}} = 1.77 \cdot \text{m}^3$

Density of fresh water  $\rho_{\text{fresh.water}} = 1000 \frac{\text{kg}}{\text{m}^3}$

Buoyancy force  $F_b = V_{\text{tot}} \cdot \rho_{\text{fresh.water}} \cdot g = 17.31 \cdot \text{kN}$

Weight of the bridge  $W_b = M_{\text{tot}} \cdot g = 18.15 \cdot \text{kN}$

Uplift force  $F_{\text{uplift}} = F_b - W_b = -0.84 \cdot \text{kN}$

The weight of the bridge equal to an equal volume of water and therefore the flange and the rods do not have to be checked.

## 9 Actions on the abutments

The actions on the abutments due to the permanent and live loads on the bridge are:

In vertical direction per abutment over the full width of the bridge

Permanent loads	$F_{v.p} = \gamma_G \cdot 0.5 M_{tot} \cdot g = 10 \cdot \text{kN}$
Live loads	$F_{v.l} = \frac{1}{2} \cdot \gamma_Q \cdot q_{fk} \cdot B_{eff} \cdot L_o = 31 \cdot \text{kN}$
Total	$F_{v.abutment} = F_{v.p} + F_{v.l} = 41 \cdot \text{kN}$
Uplift due to buoyancy	$F_{up.abutment} = \frac{F_{uplift}}{2} = -0 \cdot \text{kN}$

In longitudinal direction at the abutments

$$F_{h.x.abutment.1} = \gamma_Q \cdot Q_{fk.q} = 7 \cdot \text{kN}$$

$$F_{h.x.abutment.2} = 0 \cdot \text{kN}$$

In lateral direction per abutment

$$F_{h.y.abutment} = \frac{1}{2} \cdot \gamma_Q \cdot Q_{fk.q} = 3 \cdot \text{kN}$$

## 10 Conclusion

### SLS results

First eigenfrequency	Unloaded	$f_{0,\text{unloaded}} = 3.9 \cdot \text{Hz}$	$\geq 3.5 \text{ Hz}$
	Loaded	$f_{0,\text{loaded}} = 3.6 \cdot \text{Hz}$	$\geq 2.3 \text{ Hz}$
Deformations	LC1	$uc_{\delta,\text{LC1}} = 0.92$	$\leq 1.00$
Maximum gradient		$\varphi_{\text{max},i} = 2.8 \cdot \%$	$\leq \varphi_{\text{max}} = 4.0 \cdot \%$
Average gradient		$\varphi_{\text{avg},e} = 1.1 \cdot \%$	$\geq \varphi_{\text{avg}} = 0.5 \cdot \%$

### ULS results

Topskin	Moment	$uc_{\text{ts},\sigma} = 0.29$	$\leq 1.00$
Bottomskin	Moment	$uc_{\text{bs},\sigma} = 0.34$	$\leq 1.00$
Webs	Shear	$uc_{\text{w},\tau} = 0.78$	$\leq 1.00$
	Compression	$uc_{\text{w},\sigma} = 0.33$	$\leq 1.00$
Bolts of the railing		$uc_{\text{b},l} = (0.19 \quad 0.02 \quad 0.15)$	$\leq 1.00$
Flange	Compression around holes	$uc_{\text{f},\text{b},\sigma_{\text{yc}}} = 0.01$	$\leq 1.00$
	Tension around holes	$uc_{\text{f},\text{b},\sigma_{\text{yt}}} = 0.01$	$\leq 1.00$
	Shear around holes	$uc_{\text{f},\text{b},\tau_{\text{yz}}} = (0.00 \quad 0.18)$	$\leq 1.00$
Threaded Rods		$uc_{\text{d}} = (0.03 \quad 0.01)$	$\leq 1.00$
Support flange	Compression around holes	$uc_{\text{sf},\sigma_{\text{c}}} = (0.12 \quad 0.06)$	$\leq 1.00$
	Tension around holes	$uc_{\text{sf},\sigma_{\text{t}}} = (0.07 \quad 0.03)$	$\leq 1.00$
	Shear around holes	$uc_{\text{sf},\tau} = 0.03$	$\leq 1.00$

The bridge is checked on buoyancy and is heavy enough to counter the uplift force due to buoyancy.

### Total thermal expansion/contraction of the bridge

Length direction	Expansion	$\Delta L_{\text{dek.exp}} = 6.5 \cdot \text{mm}$
	Contraction	$\Delta L_{\text{dek.con}} = 3.9 \cdot \text{mm}$
Width direction	Expansion	$\Delta B_{\text{dek.exp}} = 1.8 \cdot \text{mm}$
	Contraction	$\Delta B_{\text{dek.con}} = 1.1 \cdot \text{mm}$

### Total thermal expansion/contraction for the dilatations

Length direction	Expansion	$\Delta L_{\text{dil.exp}} = 8.6 \cdot \text{mm}$
	Contraction	$\Delta L_{\text{dil.con}} = 5.9 \cdot \text{mm}$
Width direction	Expansion	$\Delta B_{\text{dil.exp}} = 2.4 \cdot \text{mm}$
	Contraction	$\Delta B_{\text{dil.con}} = 1.7 \cdot \text{mm}$

---

# Project Gallery


---

Cycleway Bridges.....	78
Golf Bridges.....	104
Port Bridges.....	108
Road Bridges.....	111



# Cycleway Bridges

---



## Project Number: 07-001



Location: Dronten, Netherlands  
Length: 24m  
Width: 5m  
Span: 21.5m  
Category: 5kN + Service Vehicle  
Production Year: 2007

## Project Number: 11-007



Location: Nagelervaart Netherlands  
Length: Both 20m  
Width: Bridge 1: 1.5m Bridge 2: 2.25m  
Span: Both 20m  
Category: 5kN + Service Vehicle  
Production Year: 2011



## Project Number: 12-061



Location: Aalsmeer, Aletta Jacobs  
Netherlands  
Length: 11.1m  
Width: 4.5m  
Span: 11.1m  
Category: 5kN + Service Vehicle  
Production Year: 2012



## Project Number: 11-006



Location: Borne, Netherlands  
Length: both 15m  
Width: both 4m  
Span: both 15m  
Category: 5kN + Service Vehicle  
Production Year: 2011

## Project Number: 11-018



Location: Amersfoort, Netherlands  
Length: Both 17.74m  
Width: Both 5m  
Span: Both 17.74m  
Category: 5kN + Service Vehicle  
Production Year: 2011



## Project Number: 10-026



Location: Potgieterstraat  
Rotterdam, Netherlands  
Length: 18m  
Width: 2.25m  
Span: 18m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2010



## Project number: 11-020



Location: Kamerinkse Wetering,  
Netherlands  
Length: Bridge 1: 13.8m Bridge 2: 14.9m  
Width: Both 1.5m  
Span: Bridge 1: 13.8m Bridge 2: 14.9m  
Category: 5kN/m2  
Production Year: 2011

## Project Number: 11-019



Location: Sommeldijk, Netherlands  
Length: 31m & 29m  
Width: 1.2m & 4m  
Span: In Three Parts  
Category: 5kN + Service Vehicle  
Production Year: 2012

## Project Number: 14-109



Location: Gouwebos, Netherlands  
Length: 39.1m  
Width: 4x 2.45m 1x 4m  
Span: 5 Parts  
Category: 5kN/m<sup>2</sup>  
Production Year: 2014



## Project Number: 13-067



Location: Den Oever, Netherlands  
Length: 8.5m  
Width: 2.1m  
Span: 8.5m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2013



## Project Number: 14-147



Location: Dongen, Netherlands  
Length: 14.5m  
Width: 2m  
Span: 14.5m  
Category: 5kN + Service Vehicle  
Production Year: 2014



## Project Number: 14-139



Location: Hillegersberg,  
Netherlands  
Length: 18.3m  
Width: 6.6m  
Span: 18.3m  
Category: VK35  
Production Year: 2014

## Project Number: 15-166



Exercitiesingel placed a bicycle footbridge with InfraCore® Inside. The bridge has a size of 20 meters by 1.9 meters. Yet the bridge is only 250mm thick by clamping it on its abutments and therefore the bridge has a sleek appearance. In addition, there is special aspect to this bridge that the abstract designed handrail is made entirely of fiber-reinforced polymers.

The bicycle pedestrian bridge serves as a transition to the path towards the nearby cemetery, Kralingen-Crooswijk.

Location: Exercitiesingel, Netherlands  
Length: 20m  
Width: 1.9m  
Span: 20m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2015

## Project Number: 15-167



A bicycle bridge with InfraCore® Inside was installed on 4 November for the municipality of Amersfoort.

The bridge is 20m long and 4m wide. The bicycle bridge is part of the Laak zone Phase B project and contributes to the expansion of the recreational possibilities and amenities of and along the Laak. FiberCore already provided a bridge for the Laakzone project: a traffic bridge near Bunschoten.

Location Amersfoort, Netherlands  
Length: 20m  
Width: 4m  
Span: 20m  
Category: 5kN + Service Vehicle  
Production Year: 2015



## Project Number: 13-071



Location, Beverwaard, Netherlands  
Length: variety of lengths  
Width: variety of widths  
Span: variety of spans  
Category: 33 bridges delivered  
Production Year: 2013

## Project Number: 11-035



This floating bridge was built with a different technique than Inside, the solution for the limited space under the bridge; Cyclists now have sufficient height.

Location: Uitgeest, Netherlands  
Length: 5m  
Width: 1.3m  
Span: 5m  
Category: 5 ton  
Production Year: 2004

## Project Number: 13-092



Location : Rhenen, Netherlands  
Length: 24m  
Width: 2m  
Span: 24m  
Category: Ecoduct  
Production Year: 2014



## Project Number: 14-146



Location: Malmö, Netherlands  
Length: 4.5m  
Width: 3.05m  
Span: 4.5m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2014



## Project Number: 10-005



This bicycle footbridge consists of three 12 meter bridge sections.

The contract work of this project was carried out by Haasnoot Bruggen.

Location: Hoveniersberg Roosendaal, Netherlands  
Length: 36m  
Width: 5m  
Span: 3x 12m  
Category: 5kN + Service Vehicle  
Production Year: 2010

## Project Number: 09-010



This bicycle bridge, consisting of two parts. Both parts were injected simultaneously, in 2010 this was a world record resin injection.

Location: Spoorlaan, Den Haag, Netherlands  
Length: 26.5m  
Width: 10m  
Span: 2x 13.25m  
Category: 5kN/m2  
Production Year: 2009



## Project Number: 09-014



Both bridges are very smart even though they have relatively large spans.

The railings for this project are made by contractor, Haasnoot Bruggen.

Location: Purmerend, Netherlands  
Length: Both 16m  
Width: Bridge 1: 2.5m Bridge 2: 3.75m  
Span: Both 16m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2009

## Project Number: 09-015



In collaboration with DSM, FiberCore Europe delivered a bridge to the Chinese province of Nanjing in 2009.

Before it was placed, it was exhibited at the World Expo in Shanghai.

Location: Shanghai, China  
Length: 11.5m  
Width: 2m  
Span: 11.5m  
Category: 5kN + Service Vehicle  
Production Year: 2009



## Project Number: 07-002



Location: Krimpenerwaard,  
Netherlands  
Length: 10m  
Width: 2.75m  
Span: 10m  
Category: 5kN + Service Vehicle  
Production Year: 2007



## Project Number: 13-088



Location: Kunstwerk, Netherlands  
Length: 21.5m  
Width: 3.35m  
Span: 21.5m  
Category: 5kN + Service Vehicle  
Production Year: 2013

## Project Number: 11-022



Location: Deventer, Netherlands  
Length: All 3; 22m  
Width: All 3; 2.5m  
Span: All 3; 22m  
Category: 5kN/m2  
Production Year: 2012



## Project Number: 13-101



Location: Gouderak, Netherlands  
Length: 8.5m  
Width: 3m  
Span: 8.5m  
Category: 5kN + Service Vehicle  
Production Year: 2013



## Project Number: 13-072



This beautiful bicycle bridge connects two uneven banks with each other, the south bank is higher than the north bank.

Thanks to the double bar, cycling comfort is guaranteed and an aesthetic effect is also created.

Location: Lely Maassluis, Netherlands  
Length: 10.2m  
Width: 3.5m  
Span: 10.2m  
Category: 5kN + Service Vehicle  
Production Year: 2013



## Project Number: 12-049



Location: Rozenburg, Netherlands  
Length: 26m  
Width: 1.5m  
Span: 26m  
Category: 5kN/m2  
Production Year: 2012

## Project Number: 12-060



This project was realised in cooperation with Met Janson Bridging.

Location: De Dors Zaanstad, Netherlands  
Length: 9.8m  
Width: 2.5m  
Span: 9.8m  
Category: VK30  
Production Year: 2012

## Project Number: 08-021



Location: Hoogvliet, Netherlands  
Length: 14m  
Width: 2.75m  
Span: 14m  
Category: 5kN + Service Vehicle  
Production Year: 2008/2009



## Project Number: 15-184



Location: Alkmaar, Netherlands  
Length: 12.5m  
Width: 1.52m  
Span: 12.5m  
Category: 5kN/m2  
Production Year: 2015



## Project Number: 08-001



Location: IJsselmonde, Netherlands  
Length: 9.8m  
Width: 2.75m  
Span: 9.8m  
Category: 5kN + Service Vehicle  
Production Year: 2009

## Project Number: 11-030 & 14-118



Location: Twickel, Netherlands  
Length: Both 11.24m  
Width: Both 1.6m  
Span: Both 11.24m  
Category: 5kN/m2  
Production Year: 2014



## Project Number: 15-177



Location: Grote & Terwoldse  
Wetering Heerde, Netherlands  
Length: Grote Wetering = 32m  
Terwoldse Wetering 12m  
Width: Both 2.6m  
Span: Grote Wetering = 32m  
Terwoldse Wetering 12m  
Category: 5kN/m2  
Production Year: 2015



## Project Number: 10-035



In Belgium, a new InfraCore® Inside bridge was commissioned on 8 November 2010, perhaps at one of the most special places in Flanders; the Fish Market in the historic city of Ghent.

The synthetic bridge forms an important part of the walking route through the old center of Ghent.

This bridge is unique in several respects; on the one hand, it is the first InfraCore® Inside bridge in Belgium, on the other it is also the first InfraCore® Inside bridge that is installed in a completely 17th-century environment. The modern, subdued design of the bridge forms a harmonious unity with the historical environment.

Location: Vismijn Gent, Belgium  
Length: 17.5m  
Width: 2.5m  
Span: 14.5m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2010



## Project Number: 13-099



Location: Mosselbrug Hellevoetsluis, Netherlands  
Length: 13.1m  
Width: 1.9m  
Span: 13.1m  
Category: 5kN + Service Vehicle  
Production Year: 2013



# Project number: 11-030



Location: De Zuidert, Netherlands  
Length: 3 Bridges 10.5m 2 Bridges 12.5m  
Width: All 3.1m  
Span: 3 Bridges 10.5m 2 Bridges 12.5m  
Category: 5kN/m2  
Production Year: 2011

# Project Number: 12-062



InfraCore® Inside by FiberCore Europe has landed in Italy, in the Venice-region. The 17.5m long bridge is installed in the Comune S. Stino di Livenza, a country town northeast of Venice.

The bridge will be used by pedestrian and bicycle traffic. It is probably the first all-FRP bridge in Italy.

The project has been a joint operation between FiberCore Europe and Janson Bridging Italia. The client has chosen for InfraCore® Inside because of its short lead time and low-maintenance features.

The bridge being lightweight strongly facilitated transportation and installation. InfraCore® Inside bridges have already been installed in The Netherlands, Belgium, the United Kingdom, China and the United States.

Location: Livenza, Italy  
Length: 17.5m  
Width: 2.5m  
Span: 17.5m  
Category: 5kN + Service Vehicle  
Production Year: 2013

## Project Number: 14-111



Location: Zwanenkade, Netherlands  
Length: 11.21m  
Width: 3.81m  
Span: 11.21m  
Category: 5kN + Service Vehicle  
Production Year: 2014



## Project Number: 16-209



Location: Neerwoldeiland  
Eelderwolde, Netherlands  
Length: 15m  
Width: 2.5m  
Span: 15m  
Category: 5kN/m2  
Production Year: 2016



## Project Number: 11-026



Location: Schalwijkerstraat  
Haarlem, Netherlands  
Length: 13.2m & 15m  
Width: 9.5m & 7.4m  
Span: 13.2m & 15m  
Category: 5kN + Occasional  
Vehicle  
Production Year: 2012



## Project Number: 15-177



Location: Grote & Terwoldse  
Wetering Heerde, Netherlands  
Length: Grote Wetering = 32m  
Terwoldse Wetering 12m  
Width: Both 2,6m  
Span: Grote Wetering = 32m  
Terwoldse Wetering 12m  
Category: 5kN/m2  
Production Year: 2015



## Project number: 15-149



The two bridges have been placed near the N216 for the province of Zuid-Holland, between Schoonhoven and Groot-Ammer.

Both bridges have the same dimensions, and are made with the InfraCore® Inside technology.

Location: Schoonhoven, Netherlands  
Length: Both 9m  
Width: Both 3.5m  
Span: 9m  
Category: 5kN + Service Vehicle  
Production Year: 2014



## Project Number: 13-074



Location: Zaanstad, Netherlands  
Length: 35.16m  
Width: 4.16m  
Span: In 3 Parts, 1x 15.2m 1x 5m & 1x 14.96m  
Category: 5kN + Service Vehicle  
Production Year: 2013

## First FiberCore bridge in history



This was the first bridge in the history of FCE. After realising this bridge, it was proven that with the InfraCore® technique in fact a robust bridge could be built.

The shape and section has changed over the years, the technique inside stayed the same. (see page 10. )



Location: Harlingen, Netherlands  
Length: 15m  
Width: 2.5m  
Span: 15m  
Category: 5kN/m<sup>2</sup>  
Production Year: 1997



## Project Number: 12-061



Location: Aalsmeer, Netherlands  
Length: 14.9m  
Width: 4.5m  
Span: 14.9m  
Category: 5kN + Service Vehicle  
Production Year: 2012



## Project Number: 12-056



Location, Hoogstraten, Belgium  
Length: 10m  
Width: 2.25m  
Span: 10m  
Category: 5kN/m2  
Production Year: 2012



## Project Number: 11-024

Location: Krampenloop, Netherlands  
Length: 14m  
Width: 3.2m  
Span: 14m  
Category: 5kN + Service Vehicle  
Production Year: 2011



## Project Number: 12-040

Location: Bordeaux, France  
Length: 36.05m  
Width: 2m  
Span: In 2 Parts; 1x 21.1m  
1x14.95m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2012



# Golf Bridges

---



## Project Number: 15-148



Two bridges have been placed near the N216 for the province of Zuid-Holland, between Schoonhoven & Groot-Ammer.

Both bridges have the same dimensions, and are made with the InfraCore® Inside technology.

Location: Dubai Desert Golf Club  
Length: 10m  
Width: 2.5m  
Span: 10m  
Category: 5kN + Service Vehicle  
Production Year: 2015



## Project Number: 11-008



Flanders Nippon Golf & Business Club in Hasselt / BE An impressive golf course in Belgian Limburg. The course created by Baron Rolin winds its fairways through a plain next to the Demer and between challenging ponds. Obstacles go up beautifully in this protected landscape and make the players a technically very correct game.

In the design of the plantations special attention was paid to a harmonious color choice during all seasons. Native trees, shrubs and plants form a home for the local fauna.

The course has also been developed in such a way that it is an interesting challenge for both the experienced and the less experienced golfer.

The Flanders Nippon Golf & Business Club was one of the first courses where a maintenance free InfraCore® Golf Bridge for light traffic was installed.

Location: Flanders Nippon Golf, Belgium  
Length: 6m  
Width: 3m  
Span: 6m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2011



## Project Number: 11-032



Golf course Delfland in Schipluiden / NL  
Delfland is considered by many as the nicest Pay & Play golf course in South Holland! Not for nothing the slogan is: Golf is fun & for everyone! Play inexpensively when and how often you want on our 36 holes course!

Golfbaan Delfland is located on the border of Delft and Schipluiden and is easily accessible on the A4 from both The Hague and Rotterdam in 10 to 15 minutes. In the more than 17 years of existence, the job has grown into one of the most popular and pleasant jobs in South Holland.

For young and old; beginners and advanced players and always accessible to players from other courses. Delfland golf course was the first golf course to opt for maintenance-free InfraCore® wave bridges. Meanwhile, there are already three beautiful bridges in the orbit. The first one since 2011.

Location: Golf Course Delfland, Netherlands  
Length: 7.5m  
Width: 1.5m  
Span: 7.5m  
Category: 5kN + Service Vehicle  
Production Year: 2011

## Project Number: 12-062



Wood Range Golf Club at Simi Valley / USA  
Wood Ranch Golf Club is an original design by Ted Robinson. The beautiful course is located in the rolling hills of Ventura County, less than an hour northwest of Los Angeles.

After examining the many options available, it became clear that the InfraCore® Wave Bridges offered us the best solution on all fronts; In addition to the sleek design and durability of this product, this company offered a very edge-oriented approach throughout the process, "said David Coote, Wood Estate Golf Club inspector. "In view of the trend of the golf industry with regard to choosing environmentally friendly products, InfraCore® came first."

Location: Wood Ranch Golf Club, USA  
Length: -  
Width: -  
Span: -  
Category: -  
Production Year: -

## Project Number: 11-032

The Dutch in Lingewaal / NL.  
This special Inland Links Golf course at International Championship level and designed by the famous Scottish golfer and top designer Colin Montgomerie.

The course has been constructed according to the highest European standards and is therefore the leader in terms of quality, durability and playability in the Netherlands.

Challenging for golf professionals, but also playable for the average golfer.

This 18-hole golf course is integrated in the rural area of Spijk (municipality Lingewaal). The Dutch decided to start with three ultra-slim InfraCore® Wave Bridges. The Dutch annually organizes the prestigious KLM Open, which was won in 2016 by Joost Luiten.



Location: Lingewaal, Netherlands  
Length: 9.6m  
Width: 1.9m  
Span: 9.6m  
Category: 5kN + Service Vehicle  
Production Year: 2011



## Project Number: 15-163



Location: Orlando, USA  
Length: 8.9m  
Width: 2m  
Span: 8.9m  
Category: 5kN + Service Vehicle  
Production Year: 2015

Albert Palmer's Bay Hill Club and Lodge  
in Orlando / USA

This is one of the best places in the world to stay. It was only in 1960 that the barren soil was turned into a landscape that would become known 50 years later as one of the most beautiful golf courses in the world.

Bay Hill organizes every year the Arnold Palmer Invitational presented by MasterCard. The most important golfers in the world play at this prestigious PGA tournament. "It gave me peace of mind when I heard that these bridges do not need maintenance for decades. This allows me to focus on more important issues such as course management and presentation" said Matt Beaver, superintendent at Bay Hill.

"We chose InfraCore® Golf Bridges because of the long life and sustainability of these bridges," said Roy Saunders, Bay Hill Vice President.



# Port Bridges

---





## Project Number: 14-134



The bridges are built according to a totally new bridge concept: The lattice bridge made of glass fiber instead of steel.

The bridges are in the Rotterdam port area. Matthijs Tromp tells in the interview about the many advantages of a FiberCore port bridge such as larger spans, the long, low maintenance life, the strength with respect to the weight and the specific wishes of the client.

Watch the video [here](#) explaining why we opted for the lightweight port bridges of FiberCore Europe.

Location: Hartelkanaal, Netherlands  
Length: 19.4m  
Width: 1.5m  
Span: 19.4m  
Category: 5kN/m2  
Production Year: 2015

## Project Number: 15-183

Location, Pistol &  
Madroelhaven, Netherlands  
Length: 31.4m  
Width: 1.5m  
Span: 31.4m  
Category: 5kN/m2  
Production Year: 2015



## Project Number: 16-210



Location: Calandkanaal Oost,  
Netherlands  
Length: 31.4m  
Width: 1.5m  
Span: 31.4m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2016

## Project Number: 16-220

Location Spyderbridges  
Length: 31.4m & 29m  
Width: 1.5m  
Span: 31.4m & 29m  
Category: 5kN/m<sup>2</sup>  
Production Year: 2016



# Road Bridges

---





## Project Number: 14-142



The wooden bridge deck was replaced Monday 12 January with a fiber reinforced polymer bridge deck, in which the InfraCore® Inside technology was applied.

The Friese Bridge, gateway to the city center of Alkmaar, is a bridge for all traffic. With the new deck, the bridge is ready for the coming decades.

Location: Friesebrug, Netherlands  
Length: 16.4m  
Width: 7m  
Span: 16.4m  
Category: Eurocodes  
Production Year: 2014

## Project Number: 12-052



In the end of 2012, FiberCore Europe placed, in close cooperation with construction company Haukes, a small traffic bridge in Paramaribo, Suriname.

Location: Paramaribo, Suriname,  
Netherlands  
Length: 9.5m  
Width: 3.5m  
Span: 9.5m  
Category: VK30 Bicycle, Pedestrian &  
Car Traffic  
Production Year: 2012

## Project Number: 11-001



This sustainable road bridge with InfraCore® Inside for the heaviest traffic class lies in a provincial road. The bridge even made it to the NOS journal. Here you can view the broadcast.

Location: Maarssenseweg,  
Netherlands  
Length: 6.8m  
Width: 9m  
Span: 6.8m  
Category: VK60  
Production Year: 2011



## Project Number: 15-159



Location: Brunshoten,  
Netherlands  
Length: 6.8m  
Width: 5.8m  
Span: 6.8m  
Category: Eurocodes  
Production Year: 2015



## Project number: 15-152

A road bridge with InfraCore®Inside was placed near London Wednesday 22 April.

The 13 meter long bridge (4 meters wide) has been transported to England via Vlaardingen over the water. The main contractor for the project is ECS Engineering Services.

Location: Mapledurham,  
England  
Length: 13m  
Width: 4,4m  
Span: 13m  
Category: Eurocodes  
Production year: 2015



## Project Number: 09-016



A project of 7 identical traffic bridges that each connect the public roads to a company surrounded by water.

This project is realized in close cooperation with Haasnoot Bruggen, who also delivered the railings

Location: Albrandswaard,  
Netherlands  
Length: 10.5m  
Width: 4.5m  
Span: 10.5m  
Category: VK30 Bicycle,  
Pedestrian & Car Traffic  
Production Year: 2009/2010



## Project Number: 14-119



On Friday afternoon, July 10 the bridge deck for the Crusade Bridge was transported to Utrecht.

The 15m long bridge section, fully produced with InfraCore® Inside, was transported from Rotterdam by boat, and then transported through the city center to its final destination.



Location: Kruisvaartbrug, Netherlands  
Length: 13.4m  
Width: 11.8m  
Span: 13.4m  
Category: Eurocodes  
Production Year: 2014

## Project Number: 11-012



Three traffic bridges and 2 cycle bridges, all with specially designed railings (by Ooms Construction).

Location: Wognum, Netherlands  
Length: 10 a 11 meter  
Width: Between 1.5 & 5.4m  
Span: Between 10 & 11m  
Category: van 5kN/m2 up to 45 Tons of Traffic  
Production Year: 2011

# Project Number: 11-014



This 142-meter-long traffic viaduct over the A27 is equipped with an InfraCore® Inside bridge deck of fiber-reinforced plastic.

The deck is constructed out of seven parts and has already been linked to the steel structure at the construction site. The assembled construction was then placed in its entirety over the A27 motorway.

The enormous weight savings were guiding in the choice for a composite deck, in hybrid with the steel construction. The much longer lifespan and maintenance free character of the deck also played a role.

The viaduct was built on behalf of ProRail, Heijmans was the main contractor.

Location: Lunetten, Netherlands  
Length: 140m  
Width: 6.2m  
Span: 6.2  
Category: 60 Tons of Traffic  
Production Year: 2011/2012



# How can we help?

1300 26 10 74  
[service@sisau.com.au](mailto:service@sisau.com.au)  
[sisau.com.au](http://sisau.com.au)



